



FEMALE END VIEW (J1)	MALE USB END VIEW	SPECIFICATIONS	
 1 = RED 2 = WHITE 3 = GREEN 4 = BLACK 5 = N/C 	 1 = RED (USBVCCO) 2 = WHITE (USBDO-) DATA 3 = GREEN (USBDO+) 4 = BLACK (USBGND)	CONTACT CARRIER MATERIAL/COLOR (J1)	NYLON or TPU/BLACK
		MOLDED HEAD MATERIAL/COLOR (J1)	TPU/BLACK
		CONTACT MATERIAL/PLATING (J1)	BRASS/GOLD
		HOUSING MATERIAL/FINISH (J1)	STAINLESS STEEL/PASSIVATED
		RATED CURRENT [A]	1.0 A
		RATED VOLTAGE [V]	30 V
		OUTER CABLE JACKET MATERIAL/COLOR	PVC/BLACK
		CONDUCTOR INSULATION MATERIAL	PE (DATA), PVC (POWER)
		NUMBER OF CONDUCTORS [AWG]	2x26 AWG (DATA), 2x20 AWG (POWER)
		SHIELDING	TINNED-COPPER BRAIDED
		TEMPERATURE RANGE	-20°C to +75°C (-4°F to +167°F)
		PROTECTION CLASS (J1 ONLY)	MEETS NEMA 1,3,4,6P AND IEC IP68


CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm
* UNLESS OTHERWISE SPECIFIED	

SOURCE DRAWING - FOR REFERENCE ONLY

NOTES:

1. "/C1283" DESIGNATES USB TYPE A MALE CONNECTOR WITH CUSTOM WIRING.
2. CABLE ASSEMBLY FOR EUROFAST ARE RATED AS STAND ALONE. OVERALL CABLE ASSEMBLY RATING IS THE RESPONSIBILITY OF THE CUSTOMER.

B	UPDATE TO BLACK MOLD BODY & CONTACT HOLDER	RDS	04/02/20	500000001248
REV	DESCRIPTION	BY	DATE	ECO NO.

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION 	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED. TURCK 3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us		DESCRIPTION WAKVW 4.5-3-USB/AM/C1283 IDENTIFICATION NO. 100013788 REV B		
MATERIAL		DRFT	NF	DATE	10/08/19	
FINISH		APVD		SCALE	1=1.0	
		UNIT OF MEASUREMENT MILLIMETER [INCH]		DO NOT SCALE THIS DRAWING		
		ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY CONTACT TURCK FOR MORE INFORMATION		FILE: 100013788		
				SHEET 1 OF 1		