

CERTIFICATE OF COMPLIANCE

Certificate Number 20160705-E464271
Report Reference E464271-20131122
Issue Date 2016-JULY-05

Issued to: TURCK INC
3000 CAMPUS DR
MINNEAPOLIS MN 55441-2619

**This is to certify that
representative samples of**

COMMUNICATIONS-, AUDIO/VIDEO-, DATA- AND
OTHER SIGNALING-CIRCUIT ACCESSORIES

Refer To Addendum Page For Models/Product.

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:


UL 1863 Standard for Communications-Circuit Accessories,
CAN/CSA C22.2 No. 233-M09 Standard for Cords and Cord
Sets for Communication Systems.

Additional Information:

See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>




CERTIFICATE OF COMPLIANCE

Certificate Number 20160705-E464271
Report Reference E464271-20131122
Issue Date 2016-JULY-05

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

USL, CNL – Patch Cord, Model RJ11, RJ25 or RJ45, may be followed by E or I, may be followed by S, may be followed by M, may be followed by F, may be followed by IP67, followed by RJ11, RJ25 or RJ45, followed by E or I, may be followed by S, may be followed by M, may be followed by F, may be followed by IP67, may be followed by CR, followed by 44x or 84x where x is one or two digit character specifying cable color and color code, followed by any number indicating length in meters. All part numbers may be prefixed by W indicating right angle connector. May be followed by /S or /CS followed by up to 5 digits, denoting customer options.

The IP rating (Ingress Protection Degree) has not been evaluated by UL LLC.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

