



CABLE LENGTH	TOLERANCE *				
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER				
STRIP LENGTH	TOLERANCE *				
0-7mm	±0.5mm				
8-29mm	±1.0mm				
30-49mm	±2.0mm				
50-69mm	±3.0mm				
70-100mm ±4.0mm					
OVER 100mm	100mm ±5.0mm				

* UNLESS OTHERWISE SPECIFIED

SOURCE DRAWING - FOR REFERENCE ONLY

	RELATED DOCUMENTS	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE					3000 CAMPUS NNEAPOLIS. MI	
	1. 2.		INC. U	RTY OF TURCK JSE OF THIS				1-800-544- (763) 553-7	7769
	3. 4.		WRITTEN	IENT WITHOUT PERMISSION IS OHIBITED.				(763) 553-0 www.turck.	0708 fax
	MATERIAL		DRFT	JBJ	DATE 02/14/03	DESCRIPTION	(a)	(b) (c	:)
	SEE SPECIFICATIONS	ALL DIMENSIONS DISPLAYED ON THIS	APVD		SCALE 1=1.5	VB2-PSG	3M-*/2PKG	3M-*/*	/S719
		DRAWING ARE FOR REFERENCE ONLY		UNIT OF ME	ASUREMENT				
	FINISH	REFERENCE UNLI				IDENTIFICATION N	Э.		REV
		CONTACT TURCK FOR MORE	N		ER [INCH]				
91	SEE SPECIFICATIONS	INFORMATION							
NO			l n	O NOT SCALE	THIS DRAWING	EILE: 7770005	1./	SHEET	1 05 1

NOTES:

- 1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.
- 2. "/S719" DESIGNATES SERIES WIRING.

D	UPDATE MALE COUPLING NUT	RDS	05/09/13	4019
REV	DESCRIPTION	BY	DATE	ECO NO