



CABLE LENGTH	TOLERANCE					
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER					
STRIP LENGTH	TOLERANCE					
0-7mm	±0.5mm ±1.0mm ±2.0mm					
8-29mm						
30-49mm						
50-69mm	±3.0mm					
70-100mm	±4.0mm					
OVER 100mm	±5.0mm					

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER

SPECIFIC LENGTHS. 2. "/S90" DESIGNATES THERMOPLASTIC POLYURETHANE (TPU) CABLE.				SEE SPECIFICATIONS	ALL DIMENSIONS DISPLAYED ON THIS	APVD SCALE 1=1.0		WKR 31-*-28 31/28	90		
				FINISH	DRAWING ARE FOR REFERENCE ONLY CONTACT TURCK FOR MORE	UNIT OF MEASUREMENT MILLIMETER [INCH]		IDENTIFICATION NO.		REV	
								1111011			F
F	UPDATE CABLE DIAMETER	RDS	09/26/11	36132	SEE SPECIFICATIONS	INFORMATION					'
REV	DESCRIPTION	BY	DATE	ECO NO.			DO NOT SCAL	E THIS DRAWING	FILE: 777001660 S	HEET 1	OF 1
			•				_				

3RD ANGLE PROJECTION

THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS

DOCUMENT WITHOUT WRITTEN PERMISSION IS

PROHIBITED.

DJW

RELATED DOCUMENTS

2.

3.

MATERIAL

SOURCE DRAWING - FOR REFERENCE ONLY

WKB 3T-*-SB 3T/S90

turck inc

High Technology Sensors and Automation Controls

DATE 10/10/07 DESCRIPTION

3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441

1-800-544-7769

(763) 553-7300

turck.com

(763) 553-0708 fax