

FEMALE END VIEW

1 = BROWN

2 = ORANGE

3 = BLUE

4 = WHITE

5 = GREEN

6 = YELLOW

7 = GRAY

8 = PINK

9 = RED

10 = BLACK

11 = VIOLET

12 = GREEN/YELLOW

M23 connector

PANEL CUTOUT (TYPICAL)

BASIC THRU

NON-ROTATIONAL THRU

SPECIFICATIONS

CONTACT CARRIER MATERIAL/COLOR	NYLON or PBT/GRAY
CONTACT MATERIAL/PLATING	BRASS/GOLD
CONNECTOR HOUSING MATERIAL/FINISH	STAINLESS STEEL/PASSIVATED
O-RING/GASKET MATERIAL	RUBBER (NITRILE OR FPM)
RATED CURRENT [A]	6.0 AMPS
RATED VOLTAGE [V]	300 V
CONDUCTOR INSULATION MATERIAL	PVC
NUMBER OF CONDUCTORS [AWG]	12x18 AWG
TEMPERATURE RATING	-40°C to +105°C (-40°F to +221°F)
PROTECTION CLASS	IEC IP 67
MAXIMUM PANEL THICKNESS	3.5 [0.138]

24.0 [0.94]

26.0 [1.02] REF

30.3 [1.19]

20.3 [0.80]

M20x1.5

M23x1

O-RING

GASKET

WASHER

JAM NUT

10.0 [0.39]

* METERS
SEE NOTE 1

CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm

* UNLESS OTHERWISE SPECIFIED

NOTES:

1 "*" INDICATES LEAD LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

D	RUBBER (NITRILE OR FPM)	ER	11/19/19	75412
REV	DESCRIPTION	BY	DATE	ECO. NO.

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS

1.
2.
3.
4.

3RD ANGLE PROJECTION

THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.

DRFT

APVD

JB

JD

DATE 09/03/03

SCALE 1=1.0

TURCK

3000 CAMPUS DRIVE
MINNEAPOLIS, MN 55441
1-800-544-7769
(763) 553-7300
(763) 553-0708 fax
www.turck.us

MATERIAL

SEE SPECIFICATIONS

FINISH

SEE SPECIFICATIONS

ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY

CONTACT TURCK FOR MORE INFORMATION

UNIT OF MEASUREMENT

MILLIMETER [INCH]

DESCRIPTION

CKFLV 12-12-*

IDENTIFICATION NO.

777002530

REV

D

DO NOT SCALE THIS DRAWING

FILE: 777002530

SHEET 1 OF 1