


SPECIFICATIONS				
CONTACT CARRIER MATERIAL/COLOR	TPU/BLUE-GRAY			
MOLDED MATERIAL/COLOR	TPU/BLUE-GRAY			
HOUSING MATERIAL/FINISH	STAINLESS STEEL/PASSIVATED			
CONTACT MATERIAL/PLATING	BRASS/GOLD			
RATED CURRENT [A]	4.0 A			
RATED VOLTAGE [V]	250 V			
CABLE JACKET/COLOR	PVC/GRAY			
CONDUCTOR INSULATION MATERIAL	FOAMED HDPE (DATA), PVC (POWER)			
NUMBER OF CONDUCTORS [AWG]	4x22 AWG, 22 AWG DRAIN			
SHIELDING	FOIL (PAIRS), FOIL (OVERALL)			
TEMPERATURE RATING	-30°C to +80°C (-22°F to +176°F)			
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP67			
MAX. PANEL THICKNESS	3.0 [0.12]			



CABLE LENGTH	TOLERANCE *				
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER				
STRIP LENGTH	TOLERANCE *				
0-7mm	±0.5mm				
8-29mm	±1.0mm				
30-49mm	±2.0mm				
50-69mm	±3.0mm				
70-100mm	±4.0mm				
OVER 100mm	±5.0mm				
* UNLESS OTHERWISE SPECIFIED					

NOTES:

REV DESCRIPTION

D UPDATE RATED VOLTAGE

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

RDS 08/06/19

DATE

75160

ECO NO.

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		MINNE 1- (7 (7	D CAMPUS DRIVE APOLIS, MN 55441 800-544-7769 63) 553-7300 63) 553-0708 fax www.turck.us
MATERIAL	ALL DIMENSIONS	DRFT RDS	DATE 10/20/03	DESCRIPTION FSFDV 572-*	М
DISPLAYED ON THIS		AFVD	1=1.0		
PRAWING ARE FOR REFERENCE ONLY FINISH CONTACT TURCK FOR MORE INFORMATION	UNIT OF MEASUREMENT		IDENTIFICATION NO.	REV	
	MILLIMETER [INCH]			D	
		DO NOT SCALE	THIS DRAWING	FILE: 777005177	SHEET 1 OF 1

SOURCE DRAWING - FOR REFERENCE ONLY