

FEMALE END VIEW

1 = GRAY #1
2 = GRAY #2
3 = GRAY #3
4 = GRAY #4

LOCKNUT

Ø28.6 [1.13] REF.

1/2" THREAD

SPECIFICATIONS

CONTACT CARRIER MATERIAL	NYLON OR TPU
CONTACT MATERIAL/PLATING	BRASS/GOLD
HOUSING MATERIAL	BRASS/NICKEL
O-RING MATERIAL	NITRILE
RATED CURRENT [A]	4.0 A
RATED VOLTAGE [V]	250 V
CONDUCTOR INSULATION MATERIAL	PVC
NUMBER OF CONDUCTORS [AWG]	4x18 AWG
TEMPERATURE RATING	-30°C to +80°C (-22°F to +176°F)
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP68

24.0 [0.94]

Ø25.0 [0.98] REF

KEYWAY ORIENTATION MAY VARY FROM WHAT IS SHOWN

11.5 [0.45]

21.5 [0.85]

1/2-14 NPSM

7.0 [0.28]

Ø14.1 [0.56]

M12x1

LOCKNUT

O-RING

* METERS SEE NOTE 1

CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm

* UNLESS OTHERWISE SPECIFIED

NOTES:

1. "*" INDICATES LEAD LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

2. "/S621" DESIGNATES EUROFACT RECEPTACLE WITH 18 AWG GRAY WIRES. ALL CONDUCTORS DARK GRAY AND NUMBERED TO MATCH PINOUT.

RELATED DOCUMENTS

1.
2.
3.
4.

MATERIAL

SEE SPECIFICATIONS

FINISH

SEE SPECIFICATIONS

3RD ANGLE PROJECTION

ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY

CONTACT TURCK FOR MORE INFORMATION

THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.

DRFT RWC

APVD

DATE 10/29/04

SCALE 1=.8

UNIT OF MEASUREMENT

MILLIMETER [INCH]

DO NOT SCALE THIS DRAWING

3000 CAMPUS DRIVE
MINNEAPOLIS, MN 55441
1-800-544-7769
(763) 553-7300
(763) 553-0708 fax
www.turck.us

TURCK

DESCRIPTION

FK 4.4-*/14.5/S621

IDENTIFICATION NO.

777005582

REV

D

SHEET 1 OF 1

D	UPDATE LOCKNUT	CK	01/12/11	33916
REV	DESCRIPTION	BY	DATE	ECO NO.