

The figure is a technical drawing of a RJ45 cable assembly. It includes a side view of the cable with dimensions: 15.0 [0.59] REF for the connector height, 38.0 [1.50] REF for the cable length, 14.0 [0.55] REF for the connector width, 6.3 [0.25] for the cable diameter, 9.6 [0.38] for the connector diameter, 2.5 [0.10] for the connector thickness, 18.0 [0.71] for the connector length, 6.0 [0.24] for the connector width, and 19.0 [0.75] for the connector diameter. The cable is labeled P1 and the connector is labeled J1. The drawing also includes a table with dimensions and a list of notes.

CABLE LENGTH	TOLERANCE *
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE *
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm

* UNLESS OTHERWISE SPECIFIED

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

3000 CAMPUS DRIVE
MINNEAPOLIS, MN 55441
1-800-544-7769
(763) 553-7300
(763) 553-0708 fax
www.turck.us

TURCK

DESCRIPTION
RJ45 FKFD 840-*M

IDENTIFICATION NO.

REV
O

FILE: 777005852

SHEET 1 OF 1