



VALVE END VIEW




1 = BROWN
2 = BLUE
GND = BLACK

WIRING DIAGRAM



SPECIFICATIONS

CONTACT CARRIER MATERIAL	NYLON
MOLDED HEAD MATERIAL/COLOR	TPU/TRANSLUCENT BLACK
CONTACT MATERIAL/PLATING	BRASS/SILVER
RATED CURRENT [A]	4.0 A
RATED VOLTAGE [V]	110–220 V
OUTER CABLE JACKET MATERIAL/COLOR	PVC/YELLOW
CONDUCTOR INSULATION MATERIAL	PVC
NUMBER OF CONDUCTORS [AWG]	3x24 AWG
TEMPERATURE RANGE	–40°C to +105°C (–40°F to +221°F)
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP67



* METERS
SEE NOTE 1

NOTES:

1. "*" DESIGNATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

RELATED DOCUMENTS

1.
2.
3.
4.


MATERIAL

SEE SPECIFICATIONS

FINISH

SEE SPECIFICATIONS

3RD ANGLE PROJECTION



THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.

DRFT RDS
APVD

DATE 04/13/05
SCALE 1=1.3

UNIT OF MEASUREMENT
MILLIMETER [INCH]

DO NOT SCALE THIS DRAWING

3000 CAMPUS DRIVE
MINNEAPOLIS, MN 55441
1-800-544-7769
(763) 553-7300
(763) 553-0708 fax
www.turck.us



DESCRIPTION
VAS 22-C642-*M

IDENTIFICATION NO.

REV
C

FILE: 777007102

SHEET 1 OF 1

CABLE LENGTH

TOLERANCE*

ALL LENGTHS

+ 4% (OR 50mm) OF LENGTH
- 0% (OR 0mm) OF LENGTH
WHICHEVER IS GREATER

STRIP LENGTH

TOLERANCE*

0–7mm

±0.5mm

8–29mm

±1.0mm

30–49mm

±2.0mm

50–69mm

±3.0mm

70–100mm

±4.0mm

OVER 100mm

±5.0mm

* UNLESS OTHERWISE SPECIFIED

LED AREA

LABEL SLOT

12.4 [0.49]

27.4 [1.08]

26.5 [1.04]

45.0 [1.77]

26.9 [1.06]

18.0 [0.71]

50.0 [1.97]

7.0 [0.28]

4.4 [0.17]

* METERS
SEE NOTE 1

M3x0.5 FASTENER

INTEGRAL GASKET

C

UPDATE VALVE PLUG MOLD BODY

KMY

07/31/13

42910

REV

DESCRIPTION

BY

DATE

ECO NO.