

SPECIFICATIONS				
CONTACT CARRIER MATERIAL/COLOR	TPU/GRAY			
MOLDED HEAD MATERIAL/COLOR	TPU/GRAY			
CONTACT MATERIAL/PLATING	BRASS/GOLD			
COUPLING NUT MATERIAL/PLATING	BRASS/NICKEL			
RATED CURRENT [V]	4.0 A			
RATED VOLTAGE [V]	250 V			
OUTER JACKET MATERIAL/COLOR	PVC/GRAY			
CONDUCTOR INSULATION MATERIAL	FOAMED HDPE (DATA), PVC (POWER)			
NUMBER OF CONDUCTORS [AWG]	2x16 AWG, 2x20 AWG, 20 AWG DRAIN			
SHIELD	FOIL (PAIRS), ALUM/POLYESTER FOIL (OVERALL)			
TEMPERATURE RATING	-30°C to +75°C (-22°F to +167°F)			
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP68			


SOURCE DRAWING - FOR REFERENCE ONLY

3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300

(763) 553-0708 fax www.turck.us

REV

SHEET 1 OF 1



RELATED DOCUMENTS

CABLE LENGTH	TOLERANCE *				
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER				
STRIP LENGTH	TOLERANCE *				
0-7mm	±0.5mm				
8-29mm	±1.0mm				
30-49mm	±2.0mm				
50-69mm	±3.0mm				
70-100mm	±4.0mm				
OVER 100mm	±5.0mm				
* UNILESS OTHERWISE SPECIFIED					

NOTES:

DESCRIPTION

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

CBM 04/06/1

DATE

33971 ECO NO.

DRAWING PROCESSED AS PART OF ECO 33971

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.					3000 CA MINNEAPOL 1-800- (763) (763) www.	JS, -54 553 553
MATERIAL	ALL DIMENSIONS DISPLAYED ON THIS	DRFT KF APVD	DATE 10/27/06 SCALE 1=1	DESCRIPTION	RSC	WSC	5711-*	M
	DRAWING ARE FOR REFERENCE ONLY	UNIT OF MEASUREMENT		IDENTIFICATION	I NO.			
FINISH	CONTACT TURCK FOR MORE INFORMATION	MILLIMETI	ER [INCH]					
1		DO NOT SCALE	E THIS DRAWING	FILE: 77700	7400			SHE