



CABLE LENGTH	TOLERANCE*		
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER		
STRIP LENGTH	TOLERANCE*		
0-7mm	±0.5mm		
8-29mm	±1.0mm		
30-49mm	±2.0mm		
50-69mm	±3.0mm		
70-100mm	±4.0mm		
OVER 100mm	±5.0mm		
* UNLESS OT	HERWISE SPECIFIED		

REV DESCRIPTION

	NOTES:			
	1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK SPECIFIC LENGTHS.	то с	RDER	
С	UPDATE PICOFAST COUPLING NUT PER ECO	KMY	05/15/13	40191

DATE

ECO NO.

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.	High Technology	PCK Inc	3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax turck.com
MATERIAL	ALL DIMENSIONS	DRFT RDS	DATE 08/12/05 SCALE 1=1.0	DESCRIPTION RK 4T-*-	PSW 3M
SEE SPECIFICATIONS	DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY	UNIT OF ME		IDENTIFICATION NO.	REV
FINISH	CONTACT TURCK FOR MORE	MILLIMETE	ER [INCH]		C
SEE SPECIFICATIONS	INFORMATION	DO NOT SCALE THIS DRAWING		FILE: 777008506	SHEET 1 OF 1