


SPECIFICATIONS						
CONTACT CARRIER MATERIAL	TPU					
MOLDED HEAD MATERIAL/COLOR	TPU/YELLOW					
CONTACT MATERIAL/PLATING	BRASS/GOLD					
COUPLING NUT MATERIAL/PLATING	BRASS/NICKEL					
RATED CURRENT [A]	10.0 A					
RATED VOLTAGE [V]	600 V					
OUTER JACKET MATERIAL/COLOR	PVC/YELLOW					
CONDUCTORS	3x16 AWG					
CONDUCTOR INSULATION MATERIAL	PVC					
TEMPERATURE RATING	-40°C to +105°C (-40°F to +221°F)					
PROTECTION CLASS	NEMA 1,3,4,6P,12 & IECIP67, IP68,IP69,IP69K					



CABLE LENGTH	TOLERANCE*				
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER				
STRIP LENGTH	TOLERANCE*				
0-7mm	±0.5mm				
8-29mm	±1.0mm ±2.0mm				
30-49mm					
50-69mm	±3.0mm				
70-100mm	±4.0mm				
OVER 100mm	±5.0mm				
* UNLESS OTHERWISE SPECIFIED					

CBM 04/13/21

DATE

76628

ECO NO.

## NOTES:

REV DESCRIPTION

E UPDATE PROTECTION CLASS

1. "\*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

## **⚠ WARNING:**

ELECTRICAL SHOCK HAZARD
CONNECTOR IS TO BE IN THE THE
MATED STATE WHILE ENERGIZED
REMOVE POWER BEFORE SERVICING.

## SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS  1. 2. 3. 4.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		rck	(763)	LIS, MN -544-1 553-7	55441 7769 300 708 fax
MATERIAL SEE SPECIFICATIONS	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR		DATE 05/23/12 SCALE 1=1.0 ASUREMENT	DESCRIPTION RSM RSM	36-*M		
FINISH SEE SPECIFICATIONS	REFERENCE ONLY  CONTACT TURCK FOR MORE INFORMATION	MILLIMETER [ INCH ]		IDENTIFICATION NO.			rev E
		DO NOT SCALE	THIS DRAWING	FILE: 777008704		SHEET	1 OF 1