



SPECIFICATIONS			
CONTACT CARRIER MATERIAL	TPU		
MOLDED HEAD MATERIAL/COLOR	TPU/YELLOW		
CONTACT MATERIAL/PLATING	BRASS/GOLD		
COUPLING NUT MATERIAL/FINISH	STAINLESS STEEL/PASSIVATED		
RATED CURRENT [A]	9.0 A		
RATED VOLTAGE [V]	600 V		
OUTER JACKET MATERIAL/COLOR	PVC/YELLOW		
CONDUCTOR INSULATION MATERIAL	PVC		
NUMBER OF CONDUCTORS [AWG]	4x18 AWG		
TEMPERATURE RANGE	-40°C to +105°C (-40°F to +221°F)		
PROTECTION CLASS	NEMA 1,3,4,4X,6P,12 & IECIP67,IP68,IP69,IP69K		

-	* METERS SEE NOTE 1	-
7/8-16UN #26.0 [1.02]	ø6.7 [0.27]	0 [1.97]

CABLE LENGTH	TOLERANCE *		
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER		
STRIP LENGTH	TOLERANCE *		
0-7mm	±0.5mm		
8-29mm	±1.0mm		
30-49mm	±2.0mm		
50-69mm	±3.0mm		
70-100mm	±4.0mm		
OVER 100mm	±5.0mm		
* UNLESS OTHERWISE SPECIFIED			

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

D	UPDATE PROTECTION CLASS	СВМ	04/13/21	76628
REV	DESCRIPTION	BY	DATE	ECO NO.

SOURCE DRAWING - FOR REFERENCE ONLY

2. 3. 4. PROPERTY OF TURKS INC. USE OF THIS DOCUMENT WITHOUT WRITER PERMISSION IS PROHIBITED. 1-800-544-776 (763) 553-7300 (763) 553-7300 (763) 553-07000 (763) 553-07000 (763) 553-07000 (763) 553-07000 (763) 553-07000	
3. WRITTEN PERMISSION IS (763) 553-0708	
www.turck.us	
MATERIAL DIMENSIONS DATE 06/23/08 DESCRIPTION RSV 40-*M	
ALL DIMENSIONS DISPLAYED ON THIS SCALE 1=1.0	
DRAWING ARE FOR UNIT OF MEASUREMENT UNIT OF MEASUREMENT	
FINISH IDENTIFICATION NO.	REV
CONTACT TURCK FOR MORE SFF SPECIFICATIONS INFORMATION	D
DO NOT SCALE THIS DRAWING FILE: 777008721 SHEET 1	OF 1