

| CABLE LENGTH | TOLERANCE * | | | | | | | | |
|-------------------------------|----------------------------------------------------------------------------|--|--|--|--|--|--|--|--|
| ALL LENGTHS | + 4% (OR 50mm) OF LENGT - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER | | | | | | | | |
| STRIP LENGTH | TOLERANCE * | | | | | | | | |
| 0-7mm | ±0.5mm | | | | | | | | |
| 8-29mm | ±1.0mm ±2.0mm | | | | | | | | |
| 30-49mm | | | | | | | | | |
| 50-69mm | ±3.0mm | | | | | | | | |
| 70-100mm | ±4.0mm ±5.0mm | | | | | | | | |
| OVER 100mm | | | | | | | | | |
| * UNILESS OTHERWISE SPECIFIED | | | | | | | | | |

NOTES:

| | 1. "*" INDICATES LEAD LENGTHS IN METERS. CONTACT T | MATERIAL | | DRFI | RDS | DATE 04/27/06 | RJ45 FKDD 44-*M/1 | 1 5 | | | | |
|------------------------------------------------------------|----------------------------------------------------|--------------|----------|---------|--------------------|-----------------------------------|-------------------|--------------|--------------|---------------------|------|--------|
| | SPECIFIC LENGTHS. | FIC LENGTHS. | | | | | APVD | | SCALE 1=1.0 | 1045 TROD 44-1M/ T4 | | |
| 2. THIS PRODUCT IS LIMITED TO A MAX. LENGTH OF 0.5 METERS. | | | | | SEE SPECIFICATIONS | DRAWING ARE FOR REFERENCE ONLY | UNIT OF ME | | ASUREMENT | | | - DEV |
| 1 | | | | | FINISH | | | | - f m.e 1 | IDENTIFICATION NO. | | REV |
| L | | | | | | CONTACT TURCK FOR MORE | | MILLIMETE | ER [INCH] | | | F |
| | E UPDATE MAXIMUM LENGTH | NF | 08/12/20 | 76090 | SEE SPECIFICATIONS | INFORMATION | | | | | | |
| | REV DESCRIPTION | BY | DATE | ECO NO. | | | ı | DO NOT SCALE | THIS DRAWING | FILE: 777011953 S | HEET | 1 OF 1 |
| _ | | | | | | | | | | | | |

3RD ANGLE

PROJECTION

 \odot

THIS DRAWING IS CONFIDENTIAL AND THE

PROPERTY OF TURCK INC. USE OF THIS

DOCUMENT WITHOUT WRITTEN PERMISSION IS

RELATED DOCUMENTS

2.

3.

SOURCE DRAWING - FOR REFERENCE ONLY

3000 CAMPUS DRIVE

MINNEAPOLIS, MN 55441

1-800-544-7769

(763) 553-7300

www.turck.us

(763) 553-0708 fax