



40191

ECO NO.

DATE

CABLE LENGTH	TOLERANCE *			
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER			
STRIP LENGTH	TOLERANCE *			
0-7mm	±0.5mm			
8-29mm	±1.0mm			
30-49mm	±2.0mm			
50-69mm	±3.0mm			
70-100mm	±4.0mm			
OVER 100mm	±5.0mm			
* UNLESS OTHERWISE SPECIFIED				

NOTES:

REV DESCRIPTION

ı	1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK SPECIFIC LENGTHS.	то (ORDER
В	UPDATE MALE COUPLING NUT PER ECO	KMY	05/15/13

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.	High Technology	RCK NAC ' Sensors and Automation Controls	3000 CAMPUS MINNEAPOLIS, MN 1-800-544-7 (763) 553-7 (763) 553-0 turck.com	55441 7769 300 708 fax
MATERIAL		DRFT RDS	DATE 03/09/11	DESCRIPTION RKF 4T-*-P7X	2_DSC_3M	
SEE SPECIFICATIONS	ALL DIMENSIONS DISPLAYED ON THIS	APVD	SCALE 1=1.0		Z-1 30 3W	
	DRAWING ARE FOR REFERENCE ONLY	UNIT OF ME	ASUREMENT	IDENTIFICATION NO.		REV
FINISH	CONTACT TURCK	MILLIMETE	ER[INCH]			B
SEE SPECIFICATIONS	FOR MORE INFORMATION					ט
		DO NOT SCALE	THIS DRAWING	FILE: 777015711	SHEET	1 OF 1