




MALE END VIEW	RJ11 END VIEW	WIRING DIAGRAM	SPECIFICATIONS	
 <p>1 = DRAIN 2 = N/C 3 = N/C 4 = WHITE/ORANGE 5 = GREEN (-)</p>	 <p>123456</p> <p>1 = DRAIN 2 = WHITE/ORANGE (+) 3 = N/C 4 = N/C 5 = GREEN (-) 6 = N/C</p>		CONTACT CARRIER MATERIAL (P2)	POLYCARBONATE
			CONTACT CARRIER MATERIAL (P1)	NYLON OR TPU
			MOLDED HEAD MATERIAL/COLOR (P2)	TPU/BLACK
			MOLDED HEAD MATERIAL/COLOR (P1)	TPU/YELLOW
			CONTACT MATERIAL/PLATING	BRONZE/GOLD (P2); BRASS/GOLD (P1)
			COUPLING NUT MATERIAL/PLATING (P1)	BRASS/NICKEL
			RATED CURRENT [A]	1.5 A
			RATED VOLTAGE [V]	42 V
			OUTER CABLE JACKET MATERIAL/COLOR	PVC/BLACK
			CONDUCTOR INSULATION MATERIAL	POLYOLEFIN
			NUMBER OF CONDUCTORS [AWG]	4x24 AWG, SOLID, 24 AWG DRAIN, CAT 5e
			TEMPERATURE RANGE	-40°C to +75°C (-40°F to +167°F)
			PROTECTION CLASS (RJ11)	IP20

<table><tr><th>CABLE LENGTH</th><th>TOLERANCE *</th></tr><tr><td>ALL LENGTHS</td><td>+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER</td></tr><tr><th>STRIP LENGTH</th><th>TOLERANCE *</th></tr><tr><td>0-7mm</td><td>±0.5mm</td></tr><tr><td>8-29mm</td><td>±1.0mm</td></tr><tr><td>30-49mm</td><td>±2.0mm</td></tr><tr><td>50-69mm</td><td>±3.0mm</td></tr><tr><td>70-100mm</td><td>±4.0mm</td></tr><tr><td>OVER 100mm</td><td>±5.0mm</td></tr></table> <p>* UNLESS OTHERWISE SPECIFIED</p>					CABLE LENGTH	TOLERANCE *	ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER	STRIP LENGTH	TOLERANCE *	0-7mm	±0.5mm	8-29mm	±1.0mm	30-49mm	±2.0mm	50-69mm	±3.0mm	70-100mm	±4.0mm	OVER 100mm	±5.0mm
CABLE LENGTH	TOLERANCE *																					
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER																					
STRIP LENGTH	TOLERANCE *																					
0-7mm	±0.5mm																					
8-29mm	±1.0mm																					
30-49mm	±2.0mm																					
50-69mm	±3.0mm																					
70-100mm	±4.0mm																					
OVER 100mm	±5.0mm																					
<p>NOTES:</p> <p>1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.</p> <p>2. "/C1264" DESIGNATES MALE EURO 5-PIN CONNECTOR TO RJ11 CONNECTOR WITH CUSTOM PIN OUT. CM7 OVERMOLD USED ON EUROFAST CONNECTOR.</p>																						
<p style="text-align: right;">SOURCE DRAWING - FOR REFERENCE ONLY</p>																						
<p>RELATED DOCUMENTS</p> <p>1. 2. 3. 4.</p>		<p>3RD ANGLE PROJECTION</p>	<p>THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.</p>																			
<p>MATERIAL</p> <p>SEE SPECIFICATIONS</p>		<p>DRFT RWC</p> <p>APVD</p>	<p>DATE 05/04/07</p> <p>SCALE 1=1.0</p>	<p>DESCRIPTION</p> <p>RSC RJ11 4412-*M/C1264</p>																		
<p>FINISH</p> <p>SEE SPECIFICATIONS</p>		<p>UNIT OF MEASUREMENT</p> <p>MILLIMETER [INCH]</p>		<p>IDENTIFICATION NO.</p> <p>REV</p> <p>C</p>																		
<p>C UPDATE MOLD MATERIAL DESIGNATION</p> <p>RDS 07/25/12 39475</p>		<p>DO NOT SCALE THIS DRAWING</p>		<p>FILE: 777016937</p> <p>SHEET 1 OF 1</p>																		
<p>REV DESCRIPTION</p> <p>BY DATE ECO NO.</p>																						