

The drawing shows a cable assembly with two connectors. Key dimensions include a total length of 68.5 [2.69] meters, a central section of 66.0 [2.60] meters, and a diameter of 10.0 [0.39] mm. Labels include 'CAUTION LABEL', 'STANDARD TURCK LABEL', and 'M16x0.75'. A note indicates that dimensions are in meters unless otherwise specified.

CABLE LENGTH	TOLERANCE *
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER

STRIP LENGTH	TOLERANCE *
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm

\* UNLESS OTHERWISE SPECIFIED

**CAUTION:**  
RISK OF ELECTRICAL SHOCK  
DO NOT DISCONNECT UNDER LOAD

**TURCK**

3000 CAMPUS DRIVE  
MINNEAPOLIS, MN 55441  
1-800-544-7769  
(763) 553-7300  
(763) 553-0708 fax  
www.turck.us

DRFT RWC DATE 05/16/07  
APVD SCALE 1=1.3

UNIT OF MEASUREMENT  
**MILLIMETER [ INCH ]**

DO NOT SCALE THIS DRAWING

DESCRIPTION  
BSM BKM 22-380-\*

IDENTIFICATION NO.  
REV  
H

FILE: 777017345 SHEET 1 OF 1

NOTES:  
1. "\*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

REV	DESCRIPTION	BY	DATE	ECO NO.
H	UPDATE CONDUCTOR INSULATION MATERIAL	NF	06/09/16	55092