



FEMALE END VIEW	TYPICAL PANEL CUTOUT	SPECIFICATIONS	
 1 = WHITE 2 = BROWN 3 = GREEN 4 = YELLOW 5 = GRAY 6 = PINK 7 = BLUE 8 = RED 		CONTACT CARRIER MATERIAL/COLOR	TPV/BLACK
		CONTACT MATERIAL/PLATING	BRASS/GOLD
		HOUSING/LOCKNUT MATERIAL/PLATING	STAINLESS STEEL/PASSIVATED
		O-RING MATERIAL	NITRILE
		RATED CURRENT [A]	2.0 A
		RATED VOLTAGE [V]	60 VAC/75 VDC
		CONDUCTOR INSULATION MATERIAL	PVC
		NUMBER OF CONDUCTORS [AWG]	8x24 AWG
		TEMPERATURE RANGE	-40°C to +105°C (-40°F to +221°F)
		PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP68
		MAX. PANEL THICKNESS	3.0 [0.12]

CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm
* UNLESS OTHERWISE SPECIFIED	

NOTES:

1. "*" INDICATES LEAD LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS		3RD ANGLE PROJECTION		THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax turck.com	
1. 2. 3. 4.				TURCK INC High Technology Sensors and Automation Controls			
MATERIAL		SEE SPECIFICATIONS		DRFT	RWC	DATE	09/17/07
				APVD		SCALE	1=.8
FINISH		SEE SPECIFICATIONS		UNIT OF MEASUREMENT		DESCRIPTION	
				MILLIMETER [INCH]		WD-FKFDV 8-*	
				CONTACT TURCK FOR MORE INFORMATION		IDENTIFICATION NO.	
				DO NOT SCALE THIS DRAWING		REV	
						B	
B		UPDATED CONTACT CARRIER MATERIAL		TV		07/24/15	
50675							
REV		DESCRIPTION		BY		DATE	
						ECO NO.	