





VALVE END VIEW	WIRING DIAGRAM	MALE END VIEW	SPECIFICATIONS	
 1 = RED/BLACK 2 = RED/WHITE GND = GREEN/YELLOW	VALVE P1 	 1 = GREEN/YELLOW 2 = RED/BLACK 3 = RED/WHITE 	CONTACT CARRIER MATERIAL	NYLON or TPU
			CONTACT MATERIAL/PLATING	BRASS/SILVER (VALVE), BRASS/GOLD (P1)
			MOLDED HEAD MATERIAL/COLOR	TPU/TRANSLUCENT YEL (VALVE), YEL (P1)
			COUPLING NUT MATERIAL/PLATING (P1)	BRASS/NICKEL
			RATED CURRENT	4.0 A
			RATED VOLTAGE	0-220 VAC/DC
			OUTER JACKET MATERIAL/COLOR	CPE/YELLOW
			CONDUCTOR INSULATION	EPDM
			NUMBER OF CONDUCTORS	3x18 AWG
			TEMPERATURE RATING	-40°C to +105°C (-40°F to +221°F)
			PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP67



CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm
* UNLESS OTHERWISE SPECIFIED	

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

SOURCE DRAWING - FOR REFERENCE ONLY

