





MALE END VIEW		WIRING DIAGRAM		SPECIFICATIONS																																	
 1 = RED/YELLOW 2 = WHITE/YELLOW 3 = BLACK/YELLOW 4 = DRAIN 5 = RED/GREEN 6 = WHITE/GREEN 7 = BLACK/GREEN 8 = DRAIN 9 = RED 10 = WHITE 11 = BLACK 12 = DRAIN 13 = RED/BLUE 14 = WHITE/BLUE 15 = BLACK/BLUE 16 = DRAIN 17 = ORANGE 18 = N/C 19 = DRAIN (COMMON) M23 connector				<table><tr><td>CONTACT CARRIER MATERIAL</td><td>NYLON or PBT</td></tr><tr><td>CONTACT MATERIAL/PLATING</td><td>BRASS/GOLD</td></tr><tr><td>HOUSING/LOCKNUT MATERIAL/FINISH</td><td>STAINLESS STEEL/PASSIVATED</td></tr><tr><td>O-RING/GASKET MATERIAL</td><td>RUBBER (NBR or FPM)</td></tr><tr><td>RATED CURRENT [A]</td><td>2.0 A</td></tr><tr><td>RATED VOLTAGE [V]</td><td>150 V</td></tr><tr><td>OUTER JACKET MATERIAL/COLOR</td><td>PVC/BLACK</td></tr><tr><td>CONDUCTOR INSULATION MATERIAL</td><td>PVC</td></tr><tr><td>NUMBER OF CONDUCTORS [AWG]</td><td>12x20 AWG, 1x22 AWG</td></tr><tr><td>DRAINS</td><td>4x22 AWG, 1x22 AWG</td></tr><tr><td>SHIELD</td><td>ALUM./POLYESTER FOIL</td></tr><tr><td>CONDUCTOR ARRANGEMENT</td><td>4 SHIELDED, TWISTED TRIADS WITH INDIVIDUAL DRAIN, 1 COMMUNICATION WIRE, 1 COMMON DRAIN</td></tr><tr><td>TEMPERATURE RANGE</td><td>-40°C to +105°C (-40°F to +221°F)</td></tr><tr><td>PROTECTION CLASS</td><td>MEETS IEC IP67</td></tr><tr><td>CABLE RATINGS</td><td>UL: ITC/PLTC/AWM, 105C, 300V CSA: CMG/AWM, 105C, 300V</td></tr><tr><td>MAXIMUM PANEL THICKNESS</td><td>3.5 [0.138]</td></tr></table>		CONTACT CARRIER MATERIAL	NYLON or PBT	CONTACT MATERIAL/PLATING	BRASS/GOLD	HOUSING/LOCKNUT MATERIAL/FINISH	STAINLESS STEEL/PASSIVATED	O-RING/GASKET MATERIAL	RUBBER (NBR or FPM)	RATED CURRENT [A]	2.0 A	RATED VOLTAGE [V]	150 V	OUTER JACKET MATERIAL/COLOR	PVC/BLACK	CONDUCTOR INSULATION MATERIAL	PVC	NUMBER OF CONDUCTORS [AWG]	12x20 AWG, 1x22 AWG	DRAINS	4x22 AWG, 1x22 AWG	SHIELD	ALUM./POLYESTER FOIL	CONDUCTOR ARRANGEMENT	4 SHIELDED, TWISTED TRIADS WITH INDIVIDUAL DRAIN, 1 COMMUNICATION WIRE, 1 COMMON DRAIN	TEMPERATURE RANGE	-40°C to +105°C (-40°F to +221°F)	PROTECTION CLASS	MEETS IEC IP67	CABLE RATINGS	UL: ITC/PLTC/AWM, 105C, 300V CSA: CMG/AWM, 105C, 300V	MAXIMUM PANEL THICKNESS	3.5 [0.138]
CONTACT CARRIER MATERIAL	NYLON or PBT																																				
CONTACT MATERIAL/PLATING	BRASS/GOLD																																				
HOUSING/LOCKNUT MATERIAL/FINISH	STAINLESS STEEL/PASSIVATED																																				
O-RING/GASKET MATERIAL	RUBBER (NBR or FPM)																																				
RATED CURRENT [A]	2.0 A																																				
RATED VOLTAGE [V]	150 V																																				
OUTER JACKET MATERIAL/COLOR	PVC/BLACK																																				
CONDUCTOR INSULATION MATERIAL	PVC																																				
NUMBER OF CONDUCTORS [AWG]	12x20 AWG, 1x22 AWG																																				
DRAINS	4x22 AWG, 1x22 AWG																																				
SHIELD	ALUM./POLYESTER FOIL																																				
CONDUCTOR ARRANGEMENT	4 SHIELDED, TWISTED TRIADS WITH INDIVIDUAL DRAIN, 1 COMMUNICATION WIRE, 1 COMMON DRAIN																																				
TEMPERATURE RANGE	-40°C to +105°C (-40°F to +221°F)																																				
PROTECTION CLASS	MEETS IEC IP67																																				
CABLE RATINGS	UL: ITC/PLTC/AWM, 105C, 300V CSA: CMG/AWM, 105C, 300V																																				
MAXIMUM PANEL THICKNESS	3.5 [0.138]																																				
PANEL CUTOUT (TYPICAL)																																					
																																					




CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm
* UNLESS OTHERWISE SPECIFIED	

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS		3RD ANGLE PROJECTION		THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us	
1. 2. 3. 4.				DRFT RDS		DATE 09/18/07	
MATERIAL		SEE SPECIFICATIONS		APVD		SCALE 1=1.5	
FINISH		SEE SPECIFICATIONS		UNIT OF MEASUREMENT		DESCRIPTION	
				MILLIMETER [INCH]		P-CSFLV 19-1523-*	
				CONTACT TURCK FOR MORE INFORMATION		IDENTIFICATION NO.	
				DO NOT SCALE THIS DRAWING		REV	
						F	
F UPDATE WIRING DIAGRAM (SEE ECO)		RDS 04/05/17		59541		FILE: 777020032	
REV DESCRIPTION		BY DATE		ECO NO.		SHEET 1 OF 1	