





MALE END VIEW (P1)	FEMALE END VIEW (J1,J2)	FEMALE END VIEW (J3)	SPECIFICATIONS	
		 1 = WHITE 2 = GREEN/YELLOW 3 = BLACK 4 = RED	CONTACT CARRIER MATERIAL/COLOR	TPU/BLACK
 M16 connector	 M16 connector	 M16 connector	MOLDED BODY MATERIAL/COLOR	TPU/BLACK
			CONTACT MATERIAL/PLATING	BRASS/GOLD (P1), TECU (J1-J3)
			COUPLING NUT MATERIAL/PLATING	BRASS/NICKEL
			RATED CURRENT [A]	15.0 A
			RATED VOLTAGE [V]	600 VAC/VDC
			OUTER JACKET MATERIAL/COLOR	PVC/BLACK
			CONDUCTOR INSULATION MATERIAL	PVC/NYLON (NYLON OVERCOAT)
			NUMBER OF CONDUCTORS [AWG]	4x14 AWG
			TEMPERATURE RANGE	-40°C TO +90°C (-40°F TO +194°F)
			PROTECTION CLASS	MEETS IEC IP67



CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm
* UNLESS OTHERWISE SPECIFIED	

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

**CAUTION:**
RISK OF ELECTRICAL SHOCK
DO NOT DISCONNECT UNDER LOAD

SOURCE DRAWING - FOR REFERENCE ONLY

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

⚠

CAUTION:

RISK OF ELECTRICAL SHOCK

DO NOT DISCONNECT UNDER LOAD

RELATED DOCUMENTS

1.

2.

3.

4.


MATERIAL

SEE SPECIFICATIONS

FINISH

SEE SPECIFICATIONS

3RD ANGLE PROJECTION



THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.

DRFT

RDS

DATE

09/04/08

APVD

SCALE

1=2.0

UNIT OF MEASUREMENT

MILLIMETERS

DO NOT SCALE THIS DRAWING

3000 CAMPUS DRIVE

MINNEAPOLIS, MN 55441

1-800-544-7769

(763) 553-7300

(763) 553-0708 fax

www.turck.us

TURCK

DESCRIPTION

BH-BKM/BSM/2BKM 44-193-*

IDENTIFICATION NO.

REV

H

FILE: 777022628

SHEET 1 OF 1