



FEMALE END VIEW (J1)		MALE END VIEW (P1)		SPECIFICATIONS	
 1 = BROWN 2 = WHITE 3 = BLUE 4 = BLACK 5 = GRAY		 1 = BROWN 2 = WHITE 3 = BLUE 4 = BLACK 5 = GRAY		CONTACT CARRIER MATERIAL	TPV
				MOLDED HEAD MATERIAL/COLOR	TPV/WHITE
				CONTACT MATERIAL/PLATING	BRASS/GOLD
				COUPLING NUT MATERIAL/PLATING	STAINLESS STEEL/PASSIVATED
				SHEILDING SLEEVE	STAINLESS STEEL/PASSIVATED
				RATED CURRENT [A]	4.0 A
				RATED VOLTAGE [V]	250 V
				OUTER CABLE JACKET MATERIAL/COLOR	TPV/WHITE
				CONDUCTOR INSULATION MATERIAL	POLYESTER ELASTOMER
				NUMBER OF CONDUCTORS [AWG]	5x22 AWG
				DRAIN/SHIELD	24 AWG/ALUM.-POLYESTER FOIL & T-C BRAIDED
				TEMPERATURE RANGE	-40°C to +105°C (-40°F to +221°F)
				PROTECTION CLASS	MEETS IEC IP67

CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm
* UNLESS OTHERWISE SPECIFIED	

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

2. COUPLING NUTS ARE CONNECTED TO SHIELD.

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS					3RD ANGLE PROJECTION		THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		TURCK		3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us			
1. 2. 3. 4.							DRFT *CK		DATE 11/08/10		DESCRIPTION WD-RKSV 4.5T-*--RSSV 4.5T			
MATERIAL SEE SPECIFICATIONS							APVD T.V.		SCALE 1=1.0					
FINISH SEE SPECIFICATIONS					ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY CONTACT TURCK FOR MORE INFORMATION		UNIT OF MEASUREMENT MILLIMETER [INCH]					IDENTIFICATION NO.		REV F
							DO NOT SCALE THIS DRAWING					FILE: 777026924		SHEET 1 OF 1
F		UPDATE MATERIAL SPECIFICATIONS			NF	07/21/15	50674							
REV		DESCRIPTION			BY	DATE	ECO NO.							