


FICATIONS
POLYCARBONATE
TPU/BLACK
BRONZE/GOLD
1.5 A
42 V
PVC/BLACK
POLYOLEFIN
8x26 AWG, STRANDED
26 AWG DRAIN/ALUMINIZED POLYESTER FOIL
-20°C to +75°C (-4°F to +167°F)
NEMA 1 AND IEC IP20

SOURCE DRAWING - FOR REFERENCE ONLY



RELATED DOCUMENTS 3RD ANGLE PROJECTION THIS DRAWING IS 3000 CAMPUS DRIVE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT MINNEAPOLIS, MN 55441 turck inc 1-800-544-7769 2. (763) 553-7300 WITHOUT WRITTEN PERMISSION IS High Technology Sensors and Automation Controls 3. (763) 553-0708 fax PROHIBITED. turck.com NOTES: MATERIAL DATE 02/07/1 DESCRIPTION RDS WRJ45ES RJ45S 861-\*M 1. "\*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC SCALE 1=1.0 ALL DIMENSIONS DSGN LENGTHS. DISPLAYED ON THIS DRAWING ARE FOR UNIT OF MEASUREMENT REFERENCE ONLY IDENTIFICATION NO. REV FINISH MILLIMETER [ INCH ] CONTACT TURCK FOR MORE DRAWING RELEASE 02/11/1 INFORMATION DESCRIPTION FILE: 777027264 SHEET 1 OF 1 BY DATE ECO NO. DO NOT SCALE THIS DRAWING

±5.0mm

OVER 100mm