



FEMALE END VIEW



1 = BROWN
2 = WHITE
3 = BLUE
4 = BLACK


WIRING DIAGRAM




1. +VOLTAGE (GREEN LED)
2. OUTPUT (YELLOW LED)
3. COMMON
4. OUTPUT (YELLOW LED)

SPECIFICATIONS


CONTACT CARRIER MATERIAL	TPU OR NYLON
MOLDED HEAD MATERIAL/COLOR	TPU/CLEAR
CONTACT MATERIAL/PLATING	BRASS/GOLD
COUPLING NUT MATERIAL/PLATING	BRASS/NICKEL
RATED CURRENT [A]	4.0 A
RATED VOLTAGE [V]	10-30 V
OUTER CABLE JACKET MATERIAL/COLOR	PVC/YELLOW
CONDUCTOR INSULATION MATERIAL	PVC
NUMBER OF CONDUCTORS [AWG]	4x22 AWG
TEMPERATURE RANGE	-40°C to +105°C (-40°F to +221°F)
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP68




POWER (GREEN)
OUTPUT (YELLOW)




OUTPUT (YELLOW)



44.5 [1.75]
37.0 [1.46]
J1



29.0 [1.14]
21.0 [0.83]
M12x1
Ø15.0 [0.59]



50.0 [1.97]
7.0 [0.28]
Ø5.3 [0.21]

* METERS
SEE NOTE 1

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

SOURCE DRAWING - FOR REFERENCE ONLY


RELATED DOCUMENTS

1.
2.
3.
4.

MATERIAL

FINISH

3RD ANGLE PROJECTION



ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY

CONTACT TURCK FOR MORE INFORMATION

THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.

DRFT RDS
APVD

UNIT OF MEASUREMENT
MILLIMETER [INCH]

DO NOT SCALE THIS DRAWING

3000 CAMPUS DRIVE
MINNEAPOLIS, MN 55441
1-800-544-7769
(763) 553-7300
(763) 553-0708 fax
www.turck.us



DATE 06/10/11
SCALE 1=1.0

DESCRIPTION
WK 4.43T-*--P7X3

IDENTIFICATION NO.

REV
C

C	DRAWING PROCESSED AS PART OF ECO 37652	KMY	07/23/12	37652
REV	DESCRIPTION	BY	DATE	ECO NO.