





CABLE LENGTH	TOLERANCE*				
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER				
STRIP LENGTH	TOLERANCE*				
0-7mm	±0.5mm				
8-29mm	±1.0mm				
30-49mm	±2.0mm				
50-69mm	±3.0mm				
70-100mm	±4.0mm				
OVER 100mm	±5.0mm				
* UNLESS OTHERWISE SPECIFIED					

NOTES:

1. "*" INDICATES LEAD LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS

G	UPDATE RATED VOLTAGE AND CURRENT	RDS	01/18/21	500000002372
REV	DESCRIPTION	BY	DATE	ECO NO.

CAUTION: RISK OF ELECTRICAL SHOCK DO NOT DISCONNECT UNDER LOAD

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		MINNEAPOLIS 1-800-5 (763) 5 (763) 5	IPUS DRIVE S, MN 55441 544-7769 53-7300 53-0708 fax urck.us
MATERIAL		DRFT RDS	DATE 08/06/12	DESCRIPTION OKE 40 *M (14.5	7.E. /NIDT
SEE SPECIFICATIONS	ALL DIMENSIONS DISPLAYED ON THIS	APVD M.B.	SCALE 1=1.0	P-PWR-GKDF 40-*M/14.7	/5/NP1
	DRAWING ARE FOR REFERENCE ONLY	UNIT OF MEASUREMENT		IDENTIFICATION NO.	REV
FINISH		A 40 4 40 40 40 40 40	T LINOUI 1	IDENTIFICATION NO.	KEV
SEE SPECIFICATIONS	CONTACT TURCK FOR MORE SEE SPECIFICATIONS INFORMATION		ER [INCH]		G
		DO NOT SCALE	THIS DRAWING	FILE: 777029741 S	SHEET 1 OF 1