

MALE END VIEW

1 = WHITE/ORANGE (+TX)  
2 = WHITE/GREEN (+RX)  
3 = ORANGE (-TX)  
4 = GREEN (-RX)

MALE END VIEW

1 = WHITE/ORANGE  
2 = WHITE/GREEN  
3 = GREEN  
4 = ORANGE

WIRING DIAGRAM

P1

1 <-----> 1  
2 <-----> 2  
3 <-----> 4  
4 <-----> 3

P2

SPECIFICATIONS

CONTACT CARRIER MATERIAL	TPU
MOLDED HEAD MATERIAL/COLOR	TPU/BLUE-GRAY (P1); BLACK (P2)
CONTACT MATERIAL/PLATING	BRASS/GOLD
COUPLING NUT MATERIAL/PLATING	BRASS/NICKEL
RATED CURRENT [A]	1.5 A
RATED VOLTAGE [V]	60 VAC/VDC
OUTER CABLE JACKET MATERIAL/COLOR	TPU/TEAL (HALOGEN-FREE)
CONDUCTOR INSULATION MATERIAL	PE
NUMBER OF CONDUCTORS [AWG]	4x26 AWG, STRANDED, CAT 5e
SHIELDING	ALUM.-POLYESTER FOIL AND T-C BRAIDED
TEMPERATURE RANGE	-40°C to +75°C (-40°F to +167°F)
PROTECTION CLASS	MEETS IEC IP67

\* METERS  
SEE NOTE 1

55.2 [2.17]

39.8 [1.56] REF.

15.0 [0.59]

P1

SHIELD ATTACHED TO COUPLING NUT

P2

CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm

\* UNLESS OTHERWISE SPECIFIED

NOTES:

1. "\*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

2. MULTIPROTOCOL AND ETHERCAT COMPATIBLE.

RELATED DOCUMENTS

1.

2.

3.

4.

3RD ANGLE PROJECTION

THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.

TURCK

3000 CAMPUS DRIVE  
MINNEAPOLIS, MN 55441  
1-800-544-7769  
(763) 553-7300  
(763) 553-0708 fax  
www.turck.us

MATERIAL

FINISH

DRFT RDS

APVD T.B.

DATE 09/06/12

SCALE 1=1.0

DESCRIPTION

RSSD PSGS 4M 4413-\*M

UNIT OF MEASUREMENT

MILLIMETER [ INCH ]

IDENTIFICATION NO.

REV H

DO NOT SCALE THIS DRAWING

FILE: 777030509

SHEET 1 OF 1

UPDATE VOLTAGE AND CURRENT RATINGS

DESCRIPTION

RDS

BY

DATE

ECO NO.

77278