






FEMALE END VIEW		MALE END VIEW		SPECIFICATIONS	
1 = BROWN 2 = WHITE 3 = BLUE 4 = BLACK 5 = BARE (SHIELD)		1 = BROWN 2 = WHITE 3 = BLUE 4 = BLACK 5 = BARE (SHIELD)			
 		 			
				CONTACT CARRIER MATERIAL NYLON OR TPU	
				MOLDED HEAD MATERIAL/COLOR TPU/BLACK	
				CONTACT MATERIAL/PLATING BRASS/GOLD	
				COUPLING NUT MATERIAL/FINISH STAINLESS STEEL/PASSIVATED	
				RATED CURRENT [A] 4.0 A	
				RATED VOLTAGE [V] 250 V	
				OUTER CABLE JACKET MATERIAL/COLOR PVC/YELLOW	
				CONDUCTOR INSULATION MATERIAL PVC	
				NUMBER OF CONDUCTORS [AWG] 1STPX24 AWG (DATA); 1STPX22 AWG (POWER)	
				DRAIN 24 AWG	
				SHIELDING ALUM.-POLYESTER FOIL & TINNED-COPPER BRAID	
				TEMPERATURE RANGE -40°C TO +80°C (-40°F TO +176°F)	
				PROTECTION CLASS MEETS NEMA 1,3,4,6P AND IEC IP68	





SOURCE DRAWING - FOR REFERENCE ONLY

NOTES:

- "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.
- "/S2501" DESIGNATES RFID CABLE WITH PVC JACKET AND BLACK OVERMOLD. USE "C" SIZE BODIES FOR EUROFAST CONNECTORS.

B	UPDATE CABLE USED	RDS	08/15/17	142055
REV	DESCRIPTION	BY	DATE	ECO. NO.

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION			THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.			3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us	
MATERIAL SEE SPECIFICATIONS	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY CONTACT TURCK FOR MORE INFORMATION	DRFT	RDS	DATE	02/14/14			DESCRIPTION WKV 4.5T-*--RSV 4.5T/S2501
APVD		L.H.	SCALE	1=1.0				
FINISH SEE SPECIFICATIONS		UNIT OF MEASUREMENT MILLIMETER [INCH]			IDENTIFICATION NO.			REV B
		DO NOT SCALE THIS DRAWING			FILE: 777032938			SHEET 1 OF 1