


FEMALE END VIEW




A = WHT/BLK
 B = BLK/WHT
 C = WHT/GRN
 D = GRN/WHT
 E = WHT/RED
 F = RED/WHT
 G = WHT/ORG
 H = ORG/WHT
 J = WHT/BLU
 K = BLU/WHT
 L = WHT/BRN
 M = BRN/WHT
 N = WHT/YEL
 P = YEL/WHT
 R = WHT/VIO
 S = VIO/WHT
 T = GRN/YEL
 U = GRAY
 V = N/C

CONNECTOR
 TYPE/STYLE - GT06F
 SHELL SIZE - 22
 INSERT ARRANGEMENT - 14S

SPECIFICATIONS

CONTACT CARRIER MATERIAL	NEOPRENE
CONTACT MATERIAL/PLATING	COPPER ALLOY/SILVER
HOUSING MATERIAL/PLATING	ALUMINUM ALLOY/OLIVE DRAB CHROMATE
RATED CURRENT [A]	7.0 A
RATED VOLTAGE [V]	300 V
CONDUCTOR INSULATION MATERIAL	PVC
NUMBER OF CONDUCTORS	18x18 AWG
TEMPERATURE RATING	-40°C to +105°C (-40°F to +221°F)
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP67



CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm
* UNLESS OTHERWISE SPECIFIED	

NOTES:

1. "*" INDICATES LEAD LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTH.

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS		3RD ANGLE PROJECTION		THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED. TURCK 3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us			
1. 2. 3. 4.							
MATERIAL		DRFT	RDS	DATE	02/18/14	DESCRIPTION GT00F-22-14S-1763-*	
SEE SPECIFICATIONS		APVD	J.S.	SCALE			
FINISH		UNIT OF MEASUREMENT				IDENTIFICATION NO.	
SEE SPECIFICATIONS		MILLIMETER [INCH]				REV	
		DO NOT SCALE THIS DRAWING				A	
		FILE: 777032957				SHEET 1 OF 1	

A	DRAWING RELEASE	TR	03/10/14	
REV	DESCRIPTION	BY	DATE	ECO. NO.