


WRJ45I END VIEW




12345678

- 1 = WHITE/ORANGE (+TX)
2 = ORANGE (-TX)
3 = WHITE/GREEN (+RX)
4 = N/C
5 = N/C
6 = GREEN (-RX)
7 = N/C
8 = N/C

Ethernet

RJ45 END VIEW




12345678

- 1 = WHITE/ORANGE (+TX)
2 = ORANGE (-TX)
3 = WHITE/GREEN (+RX)
4 = N/C
5 = N/C
6 = GREEN (-RX)
7 = N/C
8 = N/C

Ethernet

SPECIFICATIONS



CONTACT CARRIER MATERIAL	POLYCARBONATE
MOLDED HEAD MATERIAL/COLOR	TPU/BLACK
CONTACT MATERIAL/PLATING	BRONZE/GOLD
RATED CURRENT [A]	1.5 A
RATED VOLTAGE [V]	42 V
OUTER CABLE JACKET MATERIAL/COLOR	TPE/TEAL
CONDUCTOR INSULATION MATERIAL	HDPE
NUMBER OF CONDUCTORS [AWG]	4x24 AWG, STRANDED, CAT 5e
SHIELDING	ALUM. FOIL AND BRAIDED TINNED COPPER
TEMPERATURE RANGE	-40°C to +75°C (-40°F to +167°F)
PROTECTION CLASS	IP20



NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION 	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		<div></div> <div>3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax turck.com</div>			
	MATERIAL	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY CONTACT TURCK FOR MORE INFORMATION	DRFT	RDS	DATE	07/01/14	DESCRIPTION WRJ45I RJ45 441-*M
			APVD	T.S.	SCALE	1=1.3	
			UNIT OF MEASUREMENT MILLIMETER [INCH] DO NOT SCALE THIS DRAWING				IDENTIFICATION NO.
FINISH		FILE: 777033581				SHEET 1 OF	