


SPECI	SPECIFICATIONS					
CONTACT CARRIER MATERIAL	NYLON OR TPU					
MOLDED HEAD MATERIAL/COLOR	TPU/YELLOW					
CONTACT MATERIAL/PLATING	BRASS/GOLD					
COUPLING NUT MATERIAL/PLATING	BRASS/NICKEL					
RATED CURRENT [A]	2.0 A					
RATED VOLTAGE [V]	60 VAC/75 VDC					
OUTER CABLE JACKET MATERIAL/COLOR	TPU/BLACK					
CONDUCTOR INSULATION MATERIAL	PVC					
NUMBER OF CONDUCTORS [AWG]	8x24 AWG (4 TWISTED PAIRS)					
DRAIN/SHIELD	24 AWG DRAIN/FOIL (PAIRS), & T-C BRAID					
TEMPERATURE RANGE	-40°C to +90°C (-40°F to +194°F)					
PROTECTION CLASS	NEMA 1,3,4,6P AND IEC IP68, IP69K					



CABLE LENGTH	TOLERANCE *						
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER						
STRIP LENGTH	TOLERANCE *						
0-7mm	±0.5mm						
8-29mm	±1.0mm						
30-49mm	±2.0mm						
50-69mm	±3.0mm						
70-100mm	±4.0mm						
OVER 100mm	±5.0mm						
* UNLESS OTHERWISE SPECIFIED							

NOTES:

B UPDATE CABLE OD

REV DESCRIPTION

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

ORDER			RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCH INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION PROHIBITED.		3000 CAMPUS MINNEAPOLIS, MN 1-800-544-7 (763) 553-0 (763) 553-0 turck.com				MN 55441 7769 -7300 -0708 fax
			MATERIAL SEE SPECIFICATIONS	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY	DRFT	RDS	DATE 07/28/14	DESCRIPTION E-RKC 8T-1		1616 *	
					APVD	T.K.	SCALE 1=1.0			1010-**	
					UNIT OF MEASUREMENT			IDENTIFICATION	NO		I REV
			FINISH		MILLIMETER [INCH]			IDENTIFICATION	NO.		NEV
		40 477		CONTACT TURCK FOR MORE							B
┙	04/14/15	49433	SEE SPECIFICATIONS	INFORMATION							
	DATE	ECO NO.			DO NOT SCALE THIS DRAWING			FILE: 77703	3673	SHE	ET 1 OF 1

SOURCE DRAWING - FOR REFERENCE ONLY