


FEMALE END VIEW



1 = WHITE

2 = RED

3 = GREEN/YELLOW


4 = ORANGE

5 = BLACK

6 = BLUE

SPECIFICATIONS

DEUTSCH CONNECTOR	DT06-6S-EP11
DEUTSCH WEDGELOCK	W6S-P012
DEUTSCH TERMINALS	0462-201-16141
MOLDED HEAD MATERIAL/COLOR	TPU/BLACK
OUTER JACKET MATERIAL/COLOR	TPE/BLACK
CONDUCTOR INSULATION MATERIAL	PVC
OPERATING VOLTAGE [V]	250 V
NUMBER OF CONDUCTORS [AWG]	6x18 AWG
CABLE TEMPERATURE RANGE	-40°C to +105°C (-40°F to +221°F)
CABLE APPROVALS	TC DIRECT BURIAL, 600V, SUNLIGHT RESISTANT, OIL RESISTANT II, WTC CIC/TC, FT4, -40C COLD IMPACT



CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm

*UNLESS OTHERWISE SPECIFIED

SOURCE DRAWING - FOR REFERENCE ONLY

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

D	ADD OPERATING VOLTAGE	NF	04/25/22	77566
REV	DESCRIPTION	BY	DATE	ECO NO.

RELATED DOCUMENTS	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.	3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us	
1.		DRFT	RDS	DATE 10/13/14
2.		APVD	C.K.	SCALE 1=1.3
3.	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY	UNIT OF MEASUREMENT		
4.		MILLIMETER [INCH]		
MATERIAL	CONTACT TURCK FOR MORE INFORMATION	DESCRIPTION		
SEE SPECIFICATIONS		WDT06-6S-2132-*M		
FINISH	DO NOT SCALE THIS DRAWING	IDENTIFICATION NO.		REV
SEE SPECIFICATIONS		FILE: 777033737		D