


SPECIFICATIONS						
NUMBER OF CONDUCTORS [AWG]	3×18 AWG, 8×22 AWG					
DRAIN/SHIELD	22 AWG/ALUMINUM-POLYESTER FOIL					
CONDUCTOR INSULATION MATERIAL	PVC					
OUTER JACKET MATERIAL/COLOR	PVC/YELLOW					
HOUSING MATERIAL/COLOR	NYLON/BLACK					
RECEPTACLE MATERIAL/FINISH	STAINLESS STEEL/PASSIVATED					
CONTACT CARRIER MATERIAL	NYLON					
CONTACT MATERIAL/PLATING	BRASS/GOLD					
O-RING MATERIAL	FKM/FPM					
OPERATING VOLTAGE [V]	60 VDC					
OPERATING CURRENT [A]	4.0 AMPS/SIGNAL, 12.0 AMPS TOTAL					
PROTECTION CLASS	IP68, IP69K: ONLY WHEN ALL RECEPTACLES ARE COVERED WITH PLUGS OR CONNECTED					
OPERATING TEMPERATURE	-40°C to +85°C (-40°F to +185°F)					

WIRING DIAGRAM



SOURCE DRAWING - FOR REFERENCE ONLY

	RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.			RC		(763)	IS, MN -544-7 553-7	55441 7769 300 708 fax
	MATERIAL		DRFT	RDS	DATE 09/03/14	DESCRIPTION	HPTION 4MBV127-5-			
	SEE SPECIFICATIONS	ALL DIMENSIONS DISPLAYED ON THIS	APVD	J.S.	SCALE 1=2.0		410100122	-5-		
		DRAWING ARE FOR REFERENCE ONLY	UNIT OF ME		ASUREMENT	IDENTIFICATION NO.				REV
	FINISH	CONTACT TURCK	MILLIMETER [INCH]		IDENTIFICATION NO.				1/12	
\dashv		FOR MORE		AILLIML I L						D
4	SEE SPECIFICATIONS	INFORMATION								
			D	O NOT SCALE	THIS DRAWING	FILE: 777033899)		SHEET	1 OF 1