




FEMALE END VIEW

1 = BLACK
2 = WHITE
3 = RED
4 = GREEN/YELLOW



- 1 = BLACK
2 = WHITE
3 = RED
4 = GREEN/YELLOW

SPECIFICATIONS	
DEUTSCH CONNECTOR	DT06-4S-E008
DEUTSCH WEDGELOCK	W4S
DEUTSCH TERMINALS	0462-201-16141
RATED CURRENT [A]	10.0 A
OPERATING VOLTAGE [V]	250 [V]
MOLDED HEAD MATERIAL/COLOR	TPU/BLACK
OUTER JACKET MATERIAL/COLOR	TPE/BLACK
CONDUCTOR INSULATION MATERIAL	PVC
NUMBER OF CONDUCTORS [AWG]	4x18 AWG
PROTECTION CLASS	IP67, IP69K



CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm

*** UNLESS OTHERWISE SPECIFIED**

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.				3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us	
DRFT	RDS	DATE 01/05/15	DESCRIPTION DT06-4S-2146-*M		
APVD	A.A.	SCALE 1=1.3			
UNIT OF MEASUREMENT MILLIMETER [INCH]			IDENTIFICATION NO.		REV H
DO NOT SCALE THIS DRAWING			FILE: 777034359		SHEET 1 OF 1

H	ADD OPERATING VOLTAGE	NF	04/25/22	77566
REV	DESCRIPTION	BY	DATE	ECO NO.