


FEMALE END VIEW




A = RED
B = GREEN
C = BLACK
D = WHITE
E = DRAIN (RED/GREEN PAIR)
F = DRAIN (BLACK/WHITE PAIR)

CONNECTOR
TYPE/STYLE - MS 3116M
SHELL SIZE - 10
INSERT ARRANGEMENT - 6S

SPECIFICATIONS

CONTACT CARRIER MATERIAL	NEOPRENE
MOLDED HEAD MATERIAL/COLOR	PVC/BLACK
CONTACT MATERIAL/PLATING	COPPER ALLOY/GOLD
COUPLING NUT MATERIAL/PLATING	ALUMINUM ALLOY/OLIVE DRAB CHROMATE
MOLD SLEEVE	ALUMINUM/BLACK ANODIZED
RATED CURRENT [A]	5.6 A
RATED VOLTAGE [V]	300 V
OUTER JACKET MATERIAL/COLOR	EX60/GRAY
CONDUCTOR INSULATION MATERIAL	XLPE
NUMBER OF CONDUCTORS	5x18 AWG
CONDUCTOR ARRANGEMENT	2 SHIELDED TWISTED PAIRS W/DRAIN, 1 GND, 1 DRAIN
TEMPERATURE RATING	-60°C to +105°C (-76°F to +221°F)
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP67,IP68
CONNECTOR TYPE	MIL-DTL-26482
CABLE APPROVALS	UL: TC-ERDB, ITC-ERDB, PLTC-ERDB, 105°C, 600V -40°C COLD IMPACT; -60°C COLD BEND cUL: CIC/TC, DIRECT BURIAL, 90°C, 600V -40°C COLD IMPACT; -60°C COLD BEND




CABLE LENGTH	TOLERANCE *
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE *
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm
* UNLESS OTHERWISE SPECIFIED	

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTH.

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION 	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.				3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us			
	MATERIAL SEE SPECIFICATIONS	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY	DRFT	NF	DATE			02/16/15	DESCRIPTION MS 3116M-10-6S-2111XL-*/A
	FINISH SEE SPECIFICATIONS		APVD	J.B.	SCALE			1=1.5	
		UNIT OF MEASUREMENT MILLIMETER [INCH]		IDENTIFICATION NO.		REV D			
		DO NOT SCALE THIS DRAWING		FILE: 777034747		SHEET 1 OF 1			

D	UPDATE MOLD BODY	NF	03/13/20	500000001130
REV	DESCRIPTION	BY	DATE	ECO NO.