

The drawing shows a cable assembly with two connectors. The left connector has a length of 88.9 [3.50] REF. and a diameter of 32.0 [1.26]. The right connector has a length of 97.0 [3.82] REF. and a diameter of 34.0 [1.34]. The cable in the middle has a diameter of 11.4 [0.45]. Labels include 'CAUTION LABEL' and 'STANDARD TURCK LABEL'. A note at the top right says '* METERS SEE NOTE 1'.

CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm
* UNLESS OTHERWISE SPECIFIED	

SOURCE DRAWING - FOR REFERENCE ONLY

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTH.

RELATED DOCUMENTS		3RD ANGLE PROJECTION		THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us	
1.				DRFT	NF	DATE	03/18/15
2.				APVD		SCALE	1=2.0
3.				UNIT OF MEASUREMENT MILLIMETER [INCH]			
4.				DO NOT SCALE THIS DRAWING			
MATERIAL		ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY		DESCRIPTION GT06M-16-10S-2060-* -GT01M-16-10P			
SEE SPECIFICATIONS							
FINISH		CONTACT TURCK FOR MORE INFORMATION		IDENTIFICATION NO.			
SEE SPECIFICATIONS				REV B			
B	UPDATE CONDUCTOR COLORS	NF	12/08/17	60450	FILE: 777035084		
REV	DESCRIPTION	BY	DATE	ECO NO.	SHEET 1 OF 1		