



FEMALE END VIEW



1 = WHITE (+)
2 = BLACK (-)

SPECIFICATIONS

DEUTSCH CONNECTOR	DT06-2S-SDT-CE28
DEUTSCH WEDGELOCK	W2S-SDT-24V
DEUTSCH TERMINALS	0462-201-16141
LED COLOR	RED
RATED CURRENT (A)	12.0 A
OPERATING VOLTAGE	24 VDC
MOLDED HEAD MATERIAL/COLOR	TPU/BLACK
OUTER JACKET MATERIAL/COLOR	TPE/BLACK
CONDUCTOR INSULATION MATERIAL	PVC
NUMBER OF CONDUCTORS [AWG]	2x18 AWG
PROTECTION CLASS	IP67, IP69K




CABLE LENGTH	TOLERANCE *
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE *
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm
* UNLESS OTHERWISE SPECIFIED	

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION			THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.			3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us			
	MATERIAL	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY	DRFT	NF	DATE	11/10/16			DESCRIPTION DT06-2S-2125-*M/LED24V	
	SEE SPECIFICATIONS		APVD	A.A.	SCALE	1=1.0				
FINISH	CONTACT TURCK FOR MORE INFORMATION		UNIT OF MEASUREMENT MILLIMETER [INCH]			IDENTIFICATION NO.		REV D		
SEE SPECIFICATIONS		DO NOT SCALE THIS DRAWING			FILE: 777035102		SHEET 1 OF			

D	UPDATE PROTECTION CLASS	RDS	02/25/19	68657
REV	DESCRIPTION	BY	DATE	ECO NO.