





SPECIFICATIONS		
HOUSING MATERIAL	MATERIAL/COLOR	PBT/BLUE
CONTACT MATERIAL/PLATING		NICKEL/SILVER
RATED CURRENT [A]		40 A
RATED VOLTAGE, MAX. VOLTAGE [VAC]		480 VAC/600 VAC
CABLE GLAND MATERIAL		NYLON/BUNA-N (CABLE GRIP)
OUTER CABLE JACKET MATERIAL/COLOR		TPE/BLACK
CONDUCTOR INSULATION MATERIAL		PVC
NUMBER OF CONDUCTORS [AWG]		4x8 AWG
TEMPERATURE RANGE		-40°C to +60°C (-40°F to +140°F)
PROTECTION CLASS		IEC IP66, IP67



CABLE LENGTH	TOLERANCE *
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE *
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm
* UNLESS OTHERWISE SPECIFIED	

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS

1.
2.
3.
4.

3RD ANGLE PROJECTION

THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.

DRFT NF
APVD L.H.

DATE 06/30/15
SCALE 1=2.4

UNIT OF MEASUREMENT
MILLIMETER [INCH]

DO NOT SCALE THIS DRAWING

3000 CAMPUS DRIVE
MINNEAPOLIS, MN 55441
1-800-544-7769
(763) 553-7300
(763) 553-0708 fax
www.turck.us

TURCK

DESCRIPTION
LPS-6A-408-*

IDENTIFICATION NO.

REV
C

FILE: 777035267

SHEET 1 OF 1

C	UPDATE CONDUCTOR COLOR	NF	01/25/18	61098
REV	DESCRIPTION	BY	DATE	ECO NO.