

MALE END VIEW

CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm

* UNLESS OTHERWISE SPECIFIED

NOTES:

1. "M" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

SPECIFICATIONS				
HOUSING MATERIAL/COLOR	PBT/BLUE			
CONTACT MATERIAL/PLATING	NICKEL/SILVER			
PROTECTIVE CAP MATERIAL	NEOPRENE			
RATED CURRENT [A]	20 A			
RATED VOLTAGE/MAX. VOLTAGE [VAC]	480 VAC/600 VAC			
CABLE JACKET MATERIAL/COLOR	PVC/BLACK			
CONDUCTOR INSULATION MATERIAL	PVC			
CABLE GLAND MATERIAL	NYLON/BUNA-N (CABLE GRIP)			
NUMBERS OF CONDUCTORS [AWG]	4x12 AWG			
TEMPERATURE RATING	-40°C to +60°C (-40°F to +140°F)			
PROTECTION CLASS	IEC IP66, IP67			

3000 CAMPUS DRIVE
MINNEAPOLIS, MN 55441
1-800-544-7769
(763) 553-7300
(763) 553-0708 fax
www.turck.us

TURCK

RELATED DOCUMENTS	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us	
1. 2. 3. 4.		DRFT	NF	DATE	07/06/15
MATERIAL	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY	APVD	L.H.	SCALE	1=2.0
FINISH		UNIT OF MEASUREMENT		IDENTIFICATION NO.	
SEE SPECIFICATIONS	CONTACT TURCK FOR MORE INFORMATION	MILLIMETER [INCH]		LPS-2A-42-*/C	
SEE SPECIFICATIONS		DO NOT SCALE THIS DRAWING		REV B	

DESCRIPTION	BY	DATE	ECO. NO.
UPDATE GREEN CONDUCTOR TO GREEN/YELLOW	RDS	10/22/18	61043

FILE: 777035293

SHEET 1 OF 1