

MALE END VIEW

1 = BLACK
2 = RED
3 = WHITE
4 = GREEN/YELLOW

PANEL KNOCKOUT HOLE

CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm

* UNLESS OTHERWISE SPECIFIED

SPECIFICATIONS				
CONTACT MATERIAL/PLATING	NICKEL/SILVER			
HOUSING MATERIAL/COLOR	PBT/BLUE			
RATED CURRENT [A]	30 A			
RATED VOLTAGE/MAX. VOLTAGE [VAC]	480 VAC/600 VAC			
CONDUCTOR INSULATION MATERIAL	PVC			
NUMBERS OF CONDUCTORS [AWG]	4x10 AWG			
TEMPERATURE RATING	-40°C to +60°C (-40°F to +140°F)			
PROTECTION CLASS	IEC IP66, IP67			

SOURCE DRAWING - FOR REFERENCE ONLY

NOTES:

1. "*" INDICATES WIRE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

B	UPDATE CONDUCTOR COLOR	NF	09/01/17	61725
REV	DESCRIPTION	BY	DATE	ECO NO.

RELATED DOCUMENTS	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.	3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us	
1. 2. 3. 4.			TURCK	
MATERIAL	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY	DRFT NF	DATE 07/07/15	DESCRIPTION
SEE SPECIFICATIONS		APVD L.H.	SCALE 1=2.0	LPSF-3A-40-*/30N
FINISH	CONTACT TURCK FOR MORE INFORMATION	UNIT OF MEASUREMENT		IDENTIFICATION NO.
SEE SPECIFICATIONS		MILLIMETER [INCH]		REV
		DO NOT SCALE THIS DRAWING		B
		FILE: 777035328		SHEET 1 OF 1