



FEMALE END VIEW




1 = BLACK
2 = RED
3 = WHITE
4 = GREEN/YELLOW
5 = BLACK
6 = WHITE
7 = BROWN
8 = BLUE


PANEL KNOCKOUT HOLE



SPECIFICATIONS

CONTACT MATERIAL/PLATING	NICKEL/SILVER
HOUSING MATERIAL/COLOR	PBT/BLUE
RATED CURRENT [A]	40 A (8 AWG), 0.5 A (18 AWG)
RATED VOLTAGE/MAX. VOLTAGE [VAC]	480 VAC/600 VAC
CONDUCTOR INSULATION MATERIAL	PVC
NUMBERS OF CONDUCTORS [AWG]	4x8 AWG, 4x18 AWG
TEMPERATURE RATING	-40°C to +60°C (-40°F to +140°F)
PROTECTION CLASS	IEC IP66, IP67





NOTES:
1. "*" INDICATES WIRE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

C	UPDATED GRN CONDUCTOR TO GRN/YEL PER ECO	TV	09/18/17	62031
REV	DESCRIPTION	BY	DATE	ECO NO.

RELATED DOCUMENTS

1.
2.
3.
4.


MATERIAL

SEE SPECIFICATIONS

FINISH

SEE SPECIFICATIONS

3RD ANGLE PROJECTION



ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY

CONTACT TURCK FOR MORE INFORMATION

THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.

DRFT NF
APVD L.H.

UNIT OF MEASUREMENT
MILLIMETER [INCH]

DO NOT SCALE THIS DRAWING

3000 CAMPUS DRIVE
MINNEAPOLIS, MN 55441
1-800-544-7769
(763) 553-7300
(763) 553-0708 fax
www.turck.us

TURCK

DATE 07/07/15
SCALE 1=2.0

DESCRIPTION
LPKF-6A-408A48-* / 30N

IDENTIFICATION NO.
FILE: 777035340

REV
C

SHEET 1 OF 1