



FEMALE END VIEW



1 = BLACK
2 = RED
3 = WHITE
⏏ = GREEN/YELLOW

SPECIFICATIONS

HOUSING MATERIAL/COLOR	PBT/BLACK
CONTACT MATERIAL/PLATING	NICKEL/SILVER
DRAWPLATE MATERIAL	PLASTIC
RATED CURRENT [A]	20.0 A
RATED VOLTAGE/MAX. VOLTAGE [VAC]	480 VAC/600 VAC
CABLE GLAND MATERIAL	NYLON/BUNA-N (CABLE GRIP)
CABLE JACKET MATERIAL/COLOR	PVC/BLACK
CONDUCTOR INSULATION MATERIAL	PVC
NUMBERS OF CONDUCTORS [AWG]	4x12 AWG
TEMPERATURE RATING	-20°C to +60°C (-4°F to +140°F)
PROTECTION CLASS	MEETS IEC IP66, IP67
CABLE APPROVALS	UL: TC-ER/ITC-ER/PLTC-ER, WTTTC 105C, 600V; DIRECT BURIAL CSA: C1C/TC, 90C, 600V; FT4; IEC 60332-3-22
APPROVAL MARKING ON CONNECTOR	Ex CSA Class I, Zone 1, Ex de IIC T6*, Class II, Zone 2 Class I, Zone 1, AEx de IIC T6* Class I Division 2 Gr A,B,C,D Class II Division 2 Gr E,F,G ATEX and IECEx II 2 G/D Ex de IIC T6 *@Ta = 40°C



CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm
* UNLESS OTHERWISE SPECIFIED	

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION 	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us	
		DRFT	NF	DATE	06/24/15
		APVD	L.H.	SCALE	1=3.0
		UNIT OF MEASUREMENT		DESCRIPTION	
MATERIAL	SEE SPECIFICATIONS	MILLIMETER [INCH]		LHPK-2A-42-*/D	
FINISH	SEE SPECIFICATIONS	CONTACT TURCK FOR MORE INFORMATION		IDENTIFICATION NO.	
		DO NOT SCALE THIS DRAWING		REV	
		FILE: 777035362		B	
		SHEET 1 OF 1			

B	UPDATE GREEN CONDUCTOR TO GREEN/YELLOW	RDS	10/22/18	61043
REV	DESCRIPTION	BY	DATE	ECO NO.