


FEMALE END VIEW

1 = BLACK
2 = RED
3 = WHITE
⓪ = GREEN/YELLOW

SPECIFICATIONS

HOUSING MATERIAL/COLOR	PBT/BLACK
CONTACT MATERIAL/PLATING	NICKEL/SILVER
DRAWPLATE MATERIAL	PLASTIC
RATED CURRENT [A]	30 A
RATED VOLTAGE/MAX. VOLTAGE [VAC]	480 VAC/600 VAC
CABLE GLAND MATERIAL	NYLON/BUNA-N (CABLE GRIP)
CABLE JACKET MATERIAL/COLOR	PVC/BLACK
CONDUCTOR INSULATION MATERIAL	PVC
NUMBERS OF CONDUCTORS [AWG]	4x10 AWG
TEMPERATURE RATING	-20°C to +60°C (-4.0°F to +140°F)
PROTECTION CLASS	IEC IP66, IP67
CABLE APPROVALS	UL: TC-ER/WTTC, 90C, 600V; DIRECT BURIAL; CSA: CIC/TC, 90C, 600V; -40 COLD BEND, FT4; IEC 60332-3-22
APPROVAL MARKING ON CONNECTOR	Ex CSA Class I, Zone 1, Ex de IIC T6*, Class II, Zone 2 Class I, Zone 1, AEx de IIC T6* Class I Division 2 Gr A,B,C,D Class II Division 2 Gr E,F,G ATEX and IECEx II 2 G/D Ex de IIC T6 *@Ta = 40°C



CABLE LENGTH	TOLERANCE *
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE *
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm
* UNLESS OTHERWISE SPECIFIED	

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS

1.
2.
3.
4.

3RD ANGLE PROJECTION

THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.

DRFT
NF

DATE 06/30/15

APVD
L.H.

SCALE 1=3.0

UNIT OF MEASUREMENT

MILLIMETER [INCH]

DO NOT SCALE THIS DRAWING

3000 CAMPUS DRIVE
MINNEAPOLIS, MN 55441
1-800-544-7769
(763) 553-7300
(763) 553-0708 fax
www.turck.us

TURCK

DESCRIPTION

LHPK-3A-40-*/D

IDENTIFICATION NO.

777035365

REV

B

UPDATE CONDUCTOR COLOR

NF

08/28/17

60475

DESCRIPTION

BY

DATE

ECO NO.

SEE SPECIFICATIONS

ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY

CONTACT TURCK FOR MORE INFORMATION

SEE SPECIFICATIONS

SHEET 1 OF 1