


	SPECIFICATIONS			
	CONTACT CARRIER MATERIAL/COLOR (P2)	POLYCARBONATE/CLEAR		
	MOLDED HEAD MATERIAL/COLOR (P2)	TPU/BLACK		
	CONTACT MATERIAL/PLATING (P2)	BRONZE/GOLD		
	CONTACT CARRIER MATERIAL/COLOR (P1)	TPU/BLACK		
	MOLDED HEAD MATERIAL/COLOR (P1)	TPU/BLUE-GRAY		
	CONTACT MATERIAL/PLATING (P1)	BRASS/GOLD		
	COUPLING NUT MATERIAL/FINISH (P1)	STAINLESS STEEL/PASSIVATED		
RATED CURRENT [A]		1.5 A		
RATED VOLTAGE [V]		42 V		
	OUTER CABLE JACKET MATERIAL/COLOR	TPE/TEAL		
	CONDUCTOR INSULATION MATERIAL	HDPE		
NUMBER OF CONDUCTORS [AWG] SHIELDING TEMPERATURE RANGE		4x22 AWG, STRANDED, CAT 5e		
		ALUMPOLYESTER FOIL & T-C BRAIDED		
		-40°C to +80°C (-40°F to +176°F)		
	PROTECTION CLASS	MEETS IEC IP67 (RJ45/IP20)		
	CABLE ATTRIBUTES	UL: PLTC 75 or AWM 80C/600V		



CABLE LENGTH	TOLERANCE*			
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER			
STRIP LENGTH	TOLERANCE*			
0-7mm	±0.5mm			
8-29mm	±1.0mm			
30-49mm	±2.0mm			
50-69mm	±3.0mm			
70-100mm	±4.0mm			
OVER 100mm	0VER 100mm ±5.0mm			
* UNLESS OTHERWISE SPECIFIED				

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

Α	DRAWING RELEASE	NF	05/27/15	
REV	DESCRIPTION	BY	DATE	ECO

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION	INC. USE OF THIS		RCH Inc	3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax turck.com	
MATERIAL	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY	APVD C.K.	DATE 05/22/15 SCALE 1=1.0	DESCRIPTION RSSDV RJ45S	444-*M	
FINISH		MILLIMETER [INCH]		IDENTIFICATION NO.		REV
						Α
		DO NOT SCALE	THIS DRAWING	FILE: 777035505	SHEET	1 OF 1