


SPECIFICATIONS					
CONTACT CARRIER MATERIAL	TPU				
MOLDED HEAD MATERIAL/COLOR	TPU/BLACK				
CONTACT MATERIAL/PLATING	BRASS/GOLD				
COUPLING NUT MATERIAL/PLATING	BRASS/NICKEL				
RATED CURRENT [A]	4.0 A				
RATED VOLTAGE [V]	250 V				
OUTER CABLE JACKET MATERIAL/COLOR	TPE/BLUE				
CONDUCTOR INSULATION MATERIAL	HDPE				
NUMBER OF CONDUCTORS [AWG]	4x24 AWG, STRANDED, CAT 5e				
TEMPERATURE RANGE	-40°C to +80°C (-40°F to +176°F)				
PROTECTION CLASS	NEMA 1,3,4,6P AND IEC IP68, IP69K				



CABLE LENGTH	TOLERANCE *		
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER		
STRIP LENGTH	TOLERANCE*		
0-7mm	±0.5mm		
8-29mm	±1.0mm		
30-49mm	±2.0mm		
50-69mm	±3.0mm		
70-100mm	±4.0mm		
OVER 100mm	±5.0mm		
* UNLESS OTHERWISE SPECIFIED			

SOURCE DRAWING - FOR REFERENCE ONLY

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

2. "/S771" DESIGNATES BLACK MOLDED PLUG BODY.

NOTES:

Α	DRAWING RELEASE	TV	09/08/15	
REV	DESCRIPTION	BY	DATE	ECO

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.	3000 CAMPUS D MINNEAPOLIS, MN 1-800-544-77 (763) 553-73 (763) 553-07 turck.com			
MATERIAL	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR		DATE 09/01/15 SCALE 1=1.0	5 DESCRIPTION RSCD 440BU-*M/S771		
FINISH CONTACT TURCK FOR MORE INFORMATION		UNIT OF MEASUREMENT MILLIMETER [INCH]		IDENTIFICATION NO.		
		DO NOT SCALE THIS DRAWING		FILE: 777036045	SHEET	1 OF 1