





RELATED DOCUMENTS

2.

3.

CABLE LENGTH	TOLERANCE *
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE *
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm
* UNLESS OTHERWISE SPECIFIED	

SOURCE DRAWING - FOR REFERENCE ONLY

NOTES: 1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS. 2. "/S760" DESIGNATES BLACK CABLE JACKET. 3. "/S771" DESIGNATES BLACK MOLDED PLUG BODY.

DRAWING RELEASE 10/26/15 DESCRIPTION DATE ECO NO.

PROPERTY OF TURCK INC. USE OF THIS turck iac DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED. High Technology Sensors and Automation Controls MATERIAL DATE 10/21/15 NF SCALE 1 = 1.0 ALL DIMENSIONS L.H. SEE SPECIFICATIONS DISPLAYED ON THIS DRAWING ARE FOR UNIT OF MEASUREMENT REFERENCE ONLY FINISH CONTACT TURCK FOR MORE MILLIMETER [INCH] INFORMATION SEE SPECIFICATIONS FILE: 777036460 DO NOT SCALE THIS DRAWING

THIS DRAWING IS CONFIDENTIAL AND THE

3RD ANGLE

PROJECTION

3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax turck.com

SHEET 1 OF 1

KBE 2T-*/S760/S771

IDENTIFICATION NO. REV