

MALE END VIEW (P1)

1 = BLACK
2 = RED
3 = WHITE
GND = GRN/YEL & HSG
4 = N/C
11 = N/C
12 = N/C

FEMALE END VIEW (J1)

1 = BLACK
2 = RED
3 = WHITE
GND = GRN/YEL & HSG
4 = N/C
11 = N/C
12 = N/C

SPECIFICATIONS

CONTACT CARRIER MATERIAL/COLOR	TPE/BLACK
CONDUCTOR INSULATION MATERIAL	PVC/NYLON (NYLON OVERCOAT)
NUMBERS OF CONDUCTORS [AWG]	4x12 AWG
TEMPERATURE RANGE	-40°C TO 90°C (-40°F TO 190°F)

* METERS
SEE NOTE 1

ø17.7 [0.70]

CAUTION LABEL

TURCK LABEL

HARTING HOOD: 19120080426
HARTING CONNECTOR: 09120063041
HARTING CONTACTS: 09320006107
REMKE CORD GRIP: RSM-25212

HARTING HOOD: 19120080526
HARTING CONNECTOR: 09120063141
HARTING CONTACTS: 09320006207
REMKE CORD GRIP: RSM-25212

73.0 [2.87] REF.

48.5 [1.91]

J1

CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm

* UNLESS OTHERWISE SPECIFIED

CAUTION:
RISK OF ELECTRICAL SHOCK
DO NOT DISCONNECT UNDER LOAD

1

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

E	UPDATED DRAWING	AS	09/09/24	500000010445
REV	DESCRIPTION	BY	DATE	ECO NO.

RELATED DOCUMENTS	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us	
1.		DRFT	NF	DATE	02/29/16
2.		APVD	E.S.	SCALE	1=2.7
3.	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY	UNIT OF MEASUREMENT		DESCRIPTION	
4.		MILLIMETER [INCH]		HANQ4/2M-1668-*M-HANQW4/2F	
MATERIAL	CONTACT TURCK FOR MORE INFORMATION	DO NOT SCALE THIS DRAWING		IDENTIFICATION NO.	
SEE SPECIFICATIONS				REV	
FINISH				E	
SEE SPECIFICATIONS				FILE: 777037121	
				SHEET 1 OF 1	