

FEMALE END VIEW

1 = BROWN
2 = WHITE
3 = BLUE
4 = BLACK

WIRING DIAGRAM

1 = + VOLTAGE (GREEN LED)
2 = OUTPUT
3 = COMMON
4 = OUTPUT (YELLOW LED)

SPECIFICATIONS

CONTACT CARRIER MATERIAL	NYLON OR TPU
MOLDED HEAD MATERIAL/COLOR	TPU/CLEAR (J1), YELLOW (J2)
CONTACT MATERIAL/PLATING	BRASS/GOLD
COUPLING NUT MATERIAL/PLATING	BRASS/NICKEL
RATED CURRENT [A]	4.0 A
RATED VOLTAGE [V]	10-30 VDC
OUTER JACKET MATERIAL/COLOR	PVC/YELLOW
CONDUCTOR INSULATION MATERIAL	PVC
NUMBER OF CONDUCTORS [AWG]	4x22 AWG
TEMPERATURE RANGE	-40°C to +105°C (-40°F to +221°F)
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP68

POWER (GREEN)

OUTPUT (YELLOW)

* METERS
SEE NOTE 1

44.5 [1.75]
37.0 [1.46]
29.0 [1.14]
20.5 [0.81]
J1
M12x1
ø15.0 [0.59]
ø5.3 [0.21]
33.0 [1.30]
25.5 [1.00]
25.0 [0.98]
18.9 [0.74]
J2
M12x1
ø15.0 [0.59]

ANTI-VIBRATION DETENT

CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm

* UNLESS OTHERWISE SPECIFIED

SOURCE DRAWING - FOR REFERENCE ONLY

NOTES:

1. "*" DESIGNATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.