


MALE END VIEW



A = WHITE
B = BROWN
C = GREEN
D = YELLOW
E = GRAY
F = PINK
G = BLUE
H = RED
J = BLACK
K = VIOLET

CONNECTOR



TYPE/STYLE - MS 3110A

SHELL SIZE - 12

INSERT ARRANGEMENT - 10P

SPECIFICATIONS

CONTACT CARRIER MATERIAL	NEOPRENE
CONTACT MATERIAL/PLATING	COPPER ALLOY/GOLD
HOUSING MATERIAL/PLATING	ALUMINUM ALLOY/OLIVE DRAB CHROMATE
RATED CURRENT [A]	3.0 A
RATED VOLTAGE [V]	300 V
CONDUCTOR INSULATION MATERIAL	PVC
NUMBER OF CONDUCTORS	10x18 AWG
TEMPERATURE RATING	-40°C to +105°C (-40°F to +221°F)




CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm
*UNLESS OTHERWISE SPECIFIED	

NOTES:

1. "*" INDICATES LEAD LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		TURCK 3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us					
									
MATERIAL	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY	DRFT	TV	DATE	05/12/16	DESCRIPTION MS 3110A-12-10P-0678-*			
SEE SPECIFICATIONS		APVD	M.A.	SCALE	1=1.0				
FINISH		UNIT OF MEASUREMENT				IDENTIFICATION NO.			
SEE SPECIFICATIONS		MILLIMETER [INCH]							
		DO NOT SCALE THIS DRAWING				FILE: 777037572			
								SHEET 1 OF 1	
		CONTACT TURCK FOR MORE INFORMATION					REV		
							A		

A	DRAWING RELEASE	TV	06/01/16	
REV	DESCRIPTION	BY	DATE	ECO. NO.