




FEMALE END VIEW	MALE END VIEW	SPECIFICATIONS	
 A = WHITE B = RED C = GREEN/YELLOW D = ORANGE E = BLACK F = BLUE	 A = WHITE B = RED C = GREEN/YELLOW D = ORANGE E = BLACK F = BLUE	CONTACT CARRIER MATERIAL	NEOPRENE
CONNECTOR TYPE/STYLE – MS 3106M SHELL SIZE – 14S INSERT ARRANGEMENT – 6S	CONNECTOR TYPE/STYLE – MS 3101M SHELL SIZE – 14S INSERT ARRANGEMENT – 6P	MOLDED HEAD MATERIAL/COLOR	PVC/BLACK
		CONTACT MATERIAL/PLATING	COPPER ALLOY/SILVER
		COUPLING NUT MATERIAL/PLATING	ALUMINUM ALLOY/OLIVE DRAB CHROMATE
		MOLD SLEEVE	ALUMINUM/BLACK ANODIZED
		RATED CURRENT [A]	10.0 A
		RATED VOLTAGE [V]	200 V
		OUTER JACKET MATERIAL/COLOR	PVC/YELLOW
		CONDUCTOR INSULATION MATERIAL	PVC/NYLON
		NUMBER OF CONDUCTORS	6x18 AWG
		ARMOR SHEATH/MATERIAL	INTERLOCKING/ALUMINUM
		TEMPERATURE RATING	-40°C to +90°C (-40°F to +194°F)
		PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP67,IP68
		CONNECTOR TYPE	MIL-DTL-5015



CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm
* UNLESS OTHERWISE SPECIFIED	

NOTES:

- "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTH.
- "/S1366" DESIGNATES OVERMOLDED MIL-SPEC CONNECTOR MOLDED IN LARGER BODY SIZE TO ACCOMMODATE LARGE CABLE DIAMETER.

SOURCE DRAWING - FOR REFERENCE ONLY

<table><tr><td>50-69mm</td><td>±3.0mm</td></tr><tr><td>70-100mm</td><td>±4.0mm</td></tr><tr><td>OVER 100mm</td><td>±5.0mm</td></tr><tr><td colspan="2">* UNLESS OTHERWISE SPECIFIED</td></tr></table>					50-69mm	±3.0mm	70-100mm	±4.0mm	OVER 100mm	±5.0mm	* UNLESS OTHERWISE SPECIFIED		RELATED DOCUMENTS					3RD ANGLE PROJECTION		THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.					TURCK 3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us				
50-69mm	±3.0mm																												
70-100mm	±4.0mm																												
OVER 100mm	±5.0mm																												
* UNLESS OTHERWISE SPECIFIED																													
NOTES:					1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTH.					2. "/S1366" DESIGNATES OVERMOLDED MIL-SPEC CONNECTOR MOLDED IN LARGER BODY SIZE TO ACCOMMODATE LARGE CABLE DIAMETER.																			
C					UPDATED GRN CONDUCTOR TO GRN/YEL PER ECO					TV					01/03/18					61169									
REV					DESCRIPTION					BY					DATE					ECO NO.									
					</																								