



FEMALE END VIEW



1 = BLACK
2 = WHITE
3 = RED
4 = GREEN/YELLOW

SPECIFICATIONS

DEUTSCH CONNECTOR	DT06-4S-E008
DEUTSCH WEDGELOCK	W4S
DEUTSCH TERMINALS	0462-201-16141
RATED CURRENT [A]	10.0 A
OPERATING VOLTAGE [V]	250 V
MOLDED HEAD MATERIAL/COLOR	TPU/BLACK
OUTER JACKET MATERIAL/COLOR	TPE/BLACK
CONDUCTOR INSULATION MATERIAL	PVC
NUMBER OF CONDUCTORS [AWG]	4x18 AWG
PROTECTION CLASS	IP67, IP69K



CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm
* UNLESS OTHERWISE SPECIFIED	

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS		3RD ANGLE PROJECTION		THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED. TURCK 3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us					
1. 2. 3. 4.									
MATERIAL		DRFT	TV	DATE	11/03/16	DESCRIPTION DT06-4S-2146-*M-DT06-4S			
SEE SPECIFICATIONS		APVD	L.H.	SCALE	1=1.3				
FINISH		UNIT OF MEASUREMENT				IDENTIFICATION NO.		REV E	
SEE SPECIFICATIONS		MILLIMETER [INCH]							
		DO NOT SCALE THIS DRAWING				FILE: 777038557		SHEET 1 OF 1	

E	ADD OPERATING VOLTAGE	NF	04/25/22	77568
REV	DESCRIPTION	BY	DATE	ECO. NO.